

## Biamp P30DT-BL - Viseći zvučnik

---

Šifra: 15532

Kategorija proizvoda: Viseći Zvučnici

Proizvođač: Biamp

**Cena: 32.000,00 rsd**



### FEATURES

Installer-friendly end cap with cut-out slot and integrated magnetic closure; hides the tap selector and all cable connections

Two toolless Gripple® cable fasteners are provided for a safe, secure, and fast installation

Euroblock connector with permanent pass-through

Tap switch allows for 70V/100V or 16 ohm low impedance operation

Tuned bass reflex port for optimized low frequency performance

Loudspeaker overload protection for 24/7 failsafe operation

ETL listed to conform with UL Std 1480A; Certified to CSA C22.2#62368-1

Operating Mode	Passive
----------------	---------

Operating Environment	Indoor
-----------------------	--------

Operating Range (-10dB)	75 Hz to 20 kHz
-------------------------	-----------------

Nominal Beamwidth (H x V)	120°, conical
---------------------------	---------------

Transducers	LF 1 x 4.25" (108 mm) coated paper cone  HF 1 x 1" (25 mm) soft dome
-------------	--

Continuous Power Handling @ Nominal Impedance	Passive	28V	50W @ 16 ohms (200W peak)
--	---------	-----	---------------------------

Nominal Sensitivity @ 1m	Passive	@ 1W 87 dB	@ 2.83V 84 dB
--------------------------	---------	---------------	------------------

Nominal Maximum SPL @ 1m	Passive	Peak 110 dB	Continuous 104 dB
--------------------------	---------	----------------	----------------------

Transformer	70V: 30W, 15W, 7.5W, 3.75W, 1.75W  100V: 30W, 15W, 7.5W, 3.75W
-------------	--

Protection	Self-resetting loudspeaker protection
------------	--

## TECHNICAL SPECIFICATIONS

### APPLICATIONS

Bars and Restaurants · Hotels · Casinos Retail Outlets · Health and Fitness Clubs Houses of Worship · Exhibit Halls Corporate Meeting Rooms

### DESCRIPTION

The P30DT two-way, 4.25" pendant loudspeaker brings exceptional dispersion to areas with open ceilings, while offering clear speech and musical purity. Available in black or white, the P30DT is suitable for a wide range of background and foreground audio applications.

The Gripple cable fasteners, Euroblock connector, and 70V/100V tap switch can be hidden after installation by the innovatively designed end cap. The attractive aesthetics and ease-of-installation make this product an industry standard.

### PHYSICAL

Input Connection	4-way Euroblock connector with permanent pass-through
Controls	Power tap / low impedance selector switch
Mounting Provisions	Two 5m (16.4 ft) wire suspension cables (one as primary support, one as a safety cable), of high tensile galvanized steel wire rope with integrated spring clips for attaching the cable to the bracket and Gripple cable fasteners.
Compliance	ETL listed to comply with UL Std 1480A, Certified to CSA C22.2#62368-1  Suspension system and Gripple cable fasteners listed per UL1598 and UL2239, TUV and CSA Class 3426-01 and Class 3426-81.
Dimensions H x W	223 mm x 233 mm (8.78" x 9.17")
Weight	2.6 kg (5.7 lbs)

Finish	Refer to the Technical Drawings (page 2)
Accessories (included)	Two wire suspension cables; Two Gripple cable fasteners; End cap and cable cover
Accessory (optional)	MC-PHK16-12PK: Pendant Hanging Kit with twelve (12) 5m (16ft) lengths of Magic Cable and the connectors to suspend snap-hook-mounted pendant loudspeakers. Available in White or Black.

## TECHNICAL DRAWING / DIMENSIONS / FINISH

H x W (diameter)

223 mm x 233 mm

(8.78" x 9.17")

Unit Weight

2.6 kg (5.7 lbs) (includes cable & Gripples)

Shipping Weight

TBD

Grille:

Powder-coated perforated steel

White (RAL 9011) or Black (RAL 9010) finish

Enclosure / Finish

ABS plastic, matte finish, White or Black