© Goe not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

WHARFEDALE Diamond 12.3 White Oak Podnostojeći Zvučnik

Šifra: 15583

Kategorija prozivoda: Podnostojeći Zvučnici

Proizvođač: Wharfedale

Cena: 32.280,00 rsd

WHARFEDALE Diamond 12.3 White Oak Podnostojeći Z

Wharfedale's iconic Diamond lineage of highperformance, high-value speakers sparkles brighter than ever with the all-new Diamond 12 Series

Since 1982, Wharfedale's famous Diamond speakers have served as the classic entry point to true high-fidelity sound, their exceptional sonic value for money earning numerous 'product of the year' accolades in the UK and around the world. This autumn, with the introduction of the all-new

Diamond 12 Series, Wharfedale once again raises the bar for affordable, high-performance loudspeakers.

To develop the new range, Wharfedale has collaborated with world-renowned speaker designer Karl-Heinz Fink for the first time. Fink's track record of delivering class-leading sound from modestly priced speakers is exceptional and with the Diamond 12 Series, he and Wharfedale's team of acoustic engineers have achieved a new entry-level benchmark.

Wharfedale determined that the Diamond 12 Series should be an opportunity to start afresh. A challenge was issued to Mr Fink: how much sonic performance can you wring from a range of speakers at classic Diamond price points? And so, he and Wharfedale's team set to work, delivering clean-sheet designs without a single part unaltered from the outgoing – and more costly – Diamond 11 Series.

Klarityot The Difference is Clear

Klarity
- The
Difference
is Clear

Since

the Diamond 8 Series in 2001, Wharfedale has made the

mid/bass cones for every Diamond generation

Kevlar. 19 years and

from

many awardwining ranges later, Wharfedale has developed a new composite called Klarity™. The chief ingredient of Klarity™ polypropylene, material that has been used to make speaker cones since the BBC researched its use for this purpose in the 1970s. Polypropylene cones are renowned for their characteristically low distortion and controlled 'breakup', as well as their resistance to moisture in the air. They also have a reputation in some quarters for sounding a little

```
perception
that is
          Bass/MidoDriverspe Gone/Surround, Magnet and Voice Coil
largely
the
          Bass/Mid
result of
          Drivers
mediocre - Cone
engineeringurround,
When
          Magnet
designed
          and
and
          Voice
implemente il
optimally,
polypropylenehe
cones
          past,
can
          polypropylene
sound
          cones
enthralling<sub>have</sub>
          often
          been
          combined
          with
          high-
          damping
          surrounds
          to
          achieve
          а
          smooth
          response
          curve.
          However,
          the
          hysteresis
          of these
          surrounds
          can
          restrict
          dynamics
          and
          make
          bass
          sound a
          little
          'soft'.
          For the
          Diamond
          12
          Series,
          the aim
          was to
          combine
          the
          Klarity™
          cone
          with a
          low-
          damping
          surround,
          thereby
```

'unexciting'

achieving both low colouration and expressive dynamics. This was not a simple task but, by simulating many different cone shapes and adding ribs to provide further stiffening, a flat response curve was achieved without resorting to a highdamping surround, thereby striking the ideal balance. The Klarity™ diaphragms are driven by a substantial, precisionmade magnet system with an aluminium compensation ring to minimise the effect of variations in inductance

as the voice coil

```
travels.
This
contributes
to an
          Trebleo Unith and Grossover
absence
of
          Treble
distortion Unit
and
          and
intermodule in sover
generated
by the
          The
motor
          Diamond
system.
          12
The
          Series'
voice
          treble
coil is
          unit
wound
          sports a
on a
          25mm
high-
          dome
power
          made
epoxy/glassom a
fibre
          woven
bobbin -
          polyester
highly
          film with
unusual
          a high-
in
          loss
speakers
          coating
at this
          to
price
          deliver
level.
          open
This has
          and
the
          smoothly
advantageextended
of not
          high
adding
          frequencies.
eddy
          The
currents
          magnet
and
          system
delivering and the
greater
          front
power
          plate
handling
          have
than an
          been
{\sf aluminium}_{\sf optimised}
bobbin,
          for wide
whilst
          dispersion
also
          and
being
          uncompressed
much
          behaviour.
stiffer
          The
than the
          front
Kapton
          plate is
type.
          flat and
          exposes
          the
          dome as
          much as
          possible,
          with a
          short
          duct to
```

balance the

acoustic

load and

improve

the SPL

(sound pressure

level)

measurement.

The

treble

unit

combines

seamlessly

with the

mid/bass

driver

via a

crossover

network

using an

acoustic

LKR

24dB

topology.

This

includes

air core

inductors

of the

type

more

commonly

found in

high-end

speakers,

selected

because

they

produce

the

lowest

distortion

of all

inductor

types.

As the

resistance

of the

coil is

higher

than a

standard

laminated

steel or

ferrite

core

inductor,

the

magnetic

```
structure
of the
mid/bass
driver
          Gabinet Constructionknown
has
been
          Cabinet
modified
          Construction
compensatene
resulting cabinet
in fast,
          is a
clean
          critical
bass
          part of
with no
          any
distortion high-
from the
          performance
inductor.
          loudspeaker.
          At entry-
          level
          price
          points,
          corners
          are
          often cut
          to
          constrain
          cost, but
          this is a
          mistake;
          no
          matter
          how
          good the
          drive
          units,
          their
          performance
          will be
          wasted if
          the
          cabinet's
          construction
          suboptimal.
          For this
          reason,
          Diamond
          12
          Series
          speakers
          feature
          cabinets
          constructed
          with a
          level of
          sophistication
          usually
          reserved
          for much
          more
          expensive
```

designs. The rearported enclosure of each model is precisely sized so that the internal volume works in harmony with the drive unit system to deliver the desired sonic result. The cabinet walls are made from sections of wood fibre board of varying thickness, constructed in such a way as to subdue the identifiable characteristics of the cabinet's 'sound' and ensure the drivers' output remains unsullied. The resonant properties of each element - even the glue - were

considered

determine

the ideal

combination

of

materials

and

placement.

Inside

the

cabinet,

Intelligent

Spot

Bracing

connects

opposing

walls

with a

specific

form of

wood

brace to

achieve

optimal

reduction

of

O1

cabinet

resonance.

These

braces

are

precisely

modelled

by

computer

simulation

to

improve

upon the

commonplace

'figure of

eight'

brace,

which

can

have the

effect of

transferring

resonance

from one

wall to

another.

Speaker type	2.5-way floorstand
Enclosure type	Bass reflex
Treble driver	25mm textile dom
Mid/bass driver	130mm Klarity™ c
Dedicated bass driver	130mm Klarity™ c
Sensitivity (2.83v @ 1m)	89dB
Recommended amp power	30-150W
Peak SPL	102dB
Nominal impedance	8Ω compatible
Minimum impedance	5Ω
Frequency response (+/-3dB)	45Hz-20kHz
Bass extension (-6dB)	40Hz
Crossover frequency	2.2kHz
Dimensions (HxWxD)	975x180x320mm

Weight (each) 19.5kg Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena.