Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

ZOOM V3 - Vokalni Procesor



Šifra: 15659
Kategorija prozivoda: Digitalni Procesori
Proizvođač: ZOOM

Cena: 23.880,00 rsd

Dedicated buttons provide instant switching of the 16 onboard effects, which range from chromatic or key-based pitch correction to a talk box, vocoder, beat box, and more. You can even add up to two voices to produce thick 3-part harmonies. Plus, compression, reverb, and delay are provided with their own separate controls for further refinement of your sound.

The V3 features a high-quality mic preamp with an XLR input, switchable 48V phantom power for condenser mics, and a special Enhance function that elevates vocal clarity. A 3.5mm stereo aux input ensures that you can easily play along with music from your smartphone or backing tracks from a computer. Stereo line and headphone outputs allow simultaneous hookup to a PA system and headphones, and the headphones' volume can be independently adjusted.

Additionally, the V3 offers USB audio interface functionality, should you want to record directly to your computer for creating podcasts, song demos, YouTube videos, or more. Run the V3 for up to 3.5 hours with the supplied AA batteries, power it via USB, or connect the separately available Zoom AD-16 AC adapter for long-running projects.

Loaded with Effects

Reverb, delay, and compression with dedicated control knobs

Enhance function automatically optimizes the performance of any mic for increased clarity

Harmony function adds up to two voices to create 3-part harmonies in major and minor keys

Formant Character button alters your vocal characteristics without changing the pitch

Chromatic and key-based pitch correction

Pitch-based effects including octave, unison, deep, robot, child, and chorus

Special effects such as talk box, vocoder, beat box, whistle, distortion, and telephone

Flexible I/O

XLR mic input with switchable 48V phantom power for condenser mics

3.5mm stereo aux input allows direct connection of a mobile device or computer for music playback

1/4" stereo line outputs for hookup to a PA system or mixer

3.5mm stereo headphone output with a dedicated volume control

1/4" control input supports separately available foot controllers such as the Zoom FS01 footswitch (for toggling effects on beat) or the Zoom FS02M expression pedal (for freely modulating effect parameters)

Compatible with Zoom SGV-6 Mic

Works with the optional Zoom SGV-6 microphone

SGV-6 aids in isolating your voice by suppressing ambient noise

USB Audio Interface

Micro-USB port enables simple connectivity to your computer or mobile device for recording or streaming

2-input / 2-output USB 2.0 audio interface functionality

Supports 44.1 kHz sample rate at 16-, 24-, or 32-bit

Versatile Placement

Compact tabletop-friendly enclosure

1/4"-20 thread on rear panel for attachment to a mic stand using the separately available Zoom HRM-7 or HRM-11 mounts

Zoom V3 Specs

Effects	16 (up to Five Concurrent Effects)
Sample Rate	44.1 kHz
Bit Depth	Signal Processing: 32-Bit AD/DA Conversion: 24-Bit, 128x Oversampling
Inputs	1 x XLR 3-Pin Female Balanced Mic Input 1 x 1/8" / 3.5 mm TRS Female Unbalanced Stereo Aux Input
Outputs	2 x 1/4" TS Female Unbalanced Line Outputs 1 x 1/8" / 3.5 mm TRS Female Unbalanced Stereo Headphone Output
Control Input	1 x 1/4" TS (Compatible with Zoom FS01 and FP02M)
USB Port	1 x Micro-USB 2.0
Audio Interface	2-Input / 2-Output USB 2.0 Full Speed at 44.1 kHz / 16-, 24-, or 32-Bit
Frequency Response	20 Hz to 20 kHz (+1 dB / −3 dB, 10-Kilohm Load)
Input Gain	Mic Input: +3 to +40 dB
Input Level	Mic Input: +4 dBu (Maximum) Aux Input: -10 dBu (Rated)

Output Level	Line Outputs: +6 dBu (Maximum)
Headphone Output Power	20 mW + 20 mW into 32-Ohm Load (Maximum)
Input Impedance	Mic Input: 3 Kilohms or Greater (1 kHz) Aux Input: 22 Kilohms
Output Impedance	Line Outputs: 100 Ohms
Equivalent Input Noise	Mic Input: -125 dBu or Less (Phantom Power Off, A-Weighted, 150-Ohm Input, +40 dB Input Gain)
Noise Floor	-75 dBu
Phantom Power	+48 VDC
Power Requirements	4 x AA Batteries (Included), 5 VDC via USB Bus Power, or 9 VDC via AC Power Adapter (Available Separately)
Power Adapter	9 VDC, 500 mA (Center-Positive) via Zoom AD-16 AC Adapter (Available Separately)
Battery Life	Up to 3.5 Hours
Security	Kensington Lock Slot
Mounting	1 x 1/4"-20 Female Thread
Dimensions	5.9 x 7.5 x 2" / 15 x 19 x 5 cm
Weight	1.3 lb / 0.6 kg (Excluding Batteries)

Packaging Info

Package Weight	2.135 lb
Box Dimensions (LxWxH)	9.2 x 7 x 2.7"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.