

ZOOM ZDM1 - Podcast mikrofon

Šifra: 15658
Kategorija proizvoda: Podcast i USB Mikrofoni
Proizvođač: ZOOM

Cena: 10.680,00 rsd

electromagnetic interference from common sources such as wireless devices, power lines, computer displays, and more.

The all-metal body and grille afford ruggedness and durability for reliable use session after session. The ZDM-1 includes a pivoting mic stand mount for easy positioning and a custom windscreen for attenuation of plosives and breath noise.

Large-diaphragm dynamic design captures smooth, broadcast-quality sound

Classic end-address style

Supercardioid polar pattern provides focused pickup and excellent isolation

High 135 dB SPL handling ensures clean recordings every time

50 Hz to 18 kHz frequency response with tight bass and smooth highs enhances vocal tone for radio, podcasting, and more

Internal shockmount provides isolation from bumps and handling noise

Built-in humbucking circuit rejects electromagnetic interference

Balanced XLR output connector

All-metal body and grille stands up to daily use

Includes pivoting mic stand mount, threaded adapter, and custom windscreen

ZOOM ZDM1 - Podcast mikrofon

The large-diaphragm dynamic capsule utilizes a supercardioid pickup pattern to effectively reduce ambient sound such as room noise at the sides of the mic. To isolate the pickup element from handling noise, vibrations, and rumble, the ZDM-1 employs an integrated shock-absorbing mechanism. The ZDM-1's integral humbucking circuit improves the signal-to-noise ratio by inhibiting

Zoom ZDM-1 Specs

Microphone

Primary Applications	Studio Recording, Broadcast
Form Factor	Stand/Boom Mount
Sound Field	Mono
Operating Principle	Pressure Gradient
Capsule	1 x Dynamic
Polar Pattern	Supercardioid
Orientation	End Address
Circuitry	Solid-State
Pad	<i>None</i>
High-Pass Filter	<i>None</i>
Tone Adjustment	<i>None</i>
Indicators	<i>None</i>
On-Board Controls	<i>None</i>
Windscreen	Foam (Included)

Performance

Frequency Range	50 Hz to 18 kHz
Maximum SPL	135 dB SPL
Impedance	200 Ohms
Load Impedance	200 Ohms (Minimum)
Sensitivity	-54 dBV/Pa

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin Male
Headphone Connector	None

Physical

Color	Black
Mounting	3/8"-16 Female, 5/8"-27 Female (with Included Hardware)
Included Case	None
Included Filters	None
Construction Material	Metal
Dimensions	ø: 2.12 x L: 5.19" / ø: 5.38 x L: 13.18 cm
Weight	14.11 oz / 400 g

Packaging Info

Package Weight	1.31 lb
Box Dimensions (LxWxH)	8.4 x 5.1 x 3.5"