Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN AUDIO VIA 5004 - Razglasno pojačalo



Šifra: 16685
Kategorija prozivoda: Razglasna Pojačala
Proizvođač: Martin Audio

Cena: 575.880,00 rsd

Features
Four channels of efficient Class D amplification
5000 Watts total power output
2U rack height
Exceptionally lightweight
Switch mode power supply
Variable speed cooling fan with front-to-back airflow
Global mains operation, 115V to 230V auto-sensing
Comprehensive protection systems
Signal and clip limiter LEDs

Applications
Small to medium-scale installations
Portable sound and stage monitoring
Hotels, restaurants and bars
Houses of Worship and auditoriums
Educational facilities
Live music and dance clubs
Mobile DJ’s

Its high efficiency design reduces the energy drawn from the mains supply and ensures the power reserves needed to deliver superb sound in demanding environments with reliability and ease.

Comprehensive protection functions continuously monitor its performance to maintain safe operating conditions and full output capability in ambient temperatures up to 40°C.

For a wide variety of installations and portable situations, the VIA5004 is ideally partnered with the Martin Audio DX0.5 system processor. Larger installations will benefit from use with the DX4.0 with its on-board network capability and proprietary VU-NET software control.

GENERAL
TYPE Four-channel Class D amplifier
POWER OUTPUT *
4 x 1250W into 2 ohms
4 x 800W into 4 ohms

4 x 450W into 8 ohms
2 x 2500W bridged into 4 ohms
COOLING Vari-speed fans, front-to-back airflow
MAXIMUM AMBIENT TEMPERATURE 40°C (105°F)
AUDIO INPUTS/OUTPUTS
ANALOGUE IN/LINK (4 CHANNELS) 4 x female, 4 x male Neutrik™ XLR
ANALOGUE INPUT IMPEDANCE 10KΩ balanced
MAXIMUM ANALOGUE INPUT LEVEL +20dBu
AMPLIFIER OUTPUTS 4 x Neutrik Speakon™ NL4
AUDIO PERFORMANCE
OUTPUT NOISE -113dBA, referenced to max output
(22kHz bandwidth)
FREQUENCY RESPONSE <10Hz ->20kHz +/- 0.25dB
TOTAL HARMONIC DISTORTION <0.05% typical @ 1kHz, -3dB output (22kHz bandwidth)
SLEW RATE > 80V per microsecond
DAMPING FACTOR 120 ref 8 ohms
POWER SUPPLY
TYPE 2 x high current, high frequency switch-mode
AC OPERATING RANGE 100-240V +/-10%
45 - 65Hz
TOTAL SYSTEM EFFICIENCY > 90% typical
MAINS CONNECTOR 1 x Neutrik Powercon™
PHYSICAL
DIMENSIONS
(W) 482 x (H) 2U/88mm x (D) 441mm
(W) 19in x (H) 2U/3.5in x (D) 17.4in
incl handles and optional rear support
WEIGHT 10kg (22lbs)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.