

Polk Audio MXT30 Center Black Centralni zvučnik

Šifra: 15754

Kategorija proizvoda: Centralni Zvučnici

Proizvođač: Polk audio

Cena: 17.880,00 rsd

Polk Audio MXT30 Center Black Centralni zvučnik

CENTERPIECE OF YOUR SYSTEM

CLEAR, FOCUSED HI-RES SOUND

Monitor XT30 maximizes your enjoyment of movies, TV and gaming with crystal clear, focused dialogue, effortless bass, and dynamic, high-resolution sound. Hi-Res Audio Certified, Dolby Atmos and DTS:X compatible, and in a modern, affordable design, the MXT30 fulfills the Polk promise of great sound for all.

PURITY OF SOUND

CERTIFIED HI-RES AUDIO

PERFORMANCE

Monitor XT30's Terylene dome tweeter enables playback beyond the range of human hearing—up to 40kHz—ensuring an airy, clear, high-end energy and spaciousness that you'll not only hear but feel. Its high-resolution performance is perfect for the enjoyment of sound found in ultra-HD movies, multi-channel concert videos, and spatial audio mixed for Apple Music, Dolby Atmos, or DTS:X.

MAKING AN IMPACT

SURPRISINGLY EFFORTLESS BASS

Polk has always been known for speakers that produce effortless bass that's surprising for their size. The MXT30 is no exception. Dual 5.25" high-efficiency, dynamically balanced woofers provide a clean, open mid-range and punchy, responsive bass, with low distortion—leaving voices and music clear while filling concerts, movies and games with impact.

NO SPECIAL GEAR REQUIRED

DOLBY ATMOS

CERTIFIED & DTS:X COMPATIBLE

Compatible with the latest Dolby Atmos and DTS:X surround sound enabled AV receivers and 4- & 8-ohm amplifiers, Monitor XT does not require specialized equipment to deliver great sound.

DESIGNED BETTER

BUILT FOR PURE LISTENING

All Monitor XT models are made for the enjoyment of pure sound: Their nickel-plated binding posts guarantee a direct, lossless connection; low-resonance, critically braced, MDF cabinets isolate the sound of the woofer and tweeter without adding unwanted resonances; and their removable, precision-fit grilles minimize sonic interference.

CENTER CHANNEL SPEAKER

Qty Included	1
Width	19.9" (48.3 cm)
Height	6.50" (16.6 cm)
Depth	8.13" (20.7 cm)
Weight	13lbs (5.9 kg)
Front Array Driver Complement	<ul style="list-style-type: none">• (1) 1" (2.54 cm) Terylene Dome Tweeter• (2) 5-¼" Bi-laminate Paper Woofers
Enclosure Type	Rear port
Lower and Upper -3dB Limits	77 Hz → 26,000 Hz
Sensitivity (1 watt @ 1 meter)	89dB SPL
Total Frequency Response	55 Hz → 40,000 Hz
Recommended Amplifier Power Per Channel	30 watts → 200 watts
Tweeter/Midrange Crossover Frequency	2500 Hz
Inputs	Single nickel-plated 5-way binding posts

CABINETRY

Available Finishes	Matte black
--------------------	-------------