Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

BT-THEATRE 100MZ

Šifra: 15792
Kategorija prozivoda: TV i Pozorišna Rasveta
Proizvođač: BRITEQ



Cena: 71.880,00 rsd

Powerful 100W LED theater Fresnel with CCT= 3000K
The light output can be easily compared to that of traditional 1kW halogen theatre projectors!
Exceptional photometric / price performance: CRI / Ra >96, TLCI >97, CQS >94, Rf >92, Rg >97 !
Manual beam angle adjustment: 15° ~ 45° (field angle: 22° ~ 60°)
Color frame for use of color filters and eight-leaf barndoor included.
No more heavy and expensive dimmer packs needed!
Very silent operation: temperature controlled, low noise cooling fan.
LCD-display to navigate easily through the setup menu!
Manual or DMX-controlled: 4 different channel modes (8bit & 16bit dimming) for maximum flexibility.
Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE ! (Briteq® code: B04645)
Flicker free TV-recordings thanks to 1.2kHz LED refresh rate!
Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
Selectable lamp behavior: halogen lamp (slow) or led (fast).
Four dimmer curves: linear, square, inverse square, S-curve.
In case of DMX failure, you can choose between manual, blackout and freeze mode.
RDM-functionality for easy remote setup & monitoring: DMX addressing, channel mode, temperature, ...
Lock function to avoid unwanted altering of the settings.
Default factory settings + user settings can be saved/loaded.
3 & 5pin DMX in/outputs + ProLock in/outputs for easy daisy chaining.

General : Dimensions (cm) See drawing
General : Weight (kg) 7.2
General : Powerinput AC 100 - 240V, 50/60Hz
General : Energy Label No
General : Power consumption W 105
General : Color black
General : Display LCD
General : Fixation M12
General : IP rating indoor
Control : Modes standalone fixed, manual, DMX
Control : Protocol DMX, Wireless DMX, RDM
Control : programmable No
Control : upgradable software Yes
Control : minimum DMX channels 1
Control : maximum DMX channels 4
Light : lamp socket No

Light : Lux 2630 (@ 5m beam 16°)
Light : lamp COB
Light : min. color temperature (K) 3000
Light : max. color temperature (K) 3000
Light : CRI 95
Light : colors White, Warm white
Light : mix colors No
Light : functions manual focus, manual zoom
Light : min. beam angle (°) 15
Light : max. beam angle (°) 45
Light : max. refresh rate (kHz) 1.2
Connections : input 3 pin XLR, 5 pin XLR, wireless DMX optional, usb, PowerCon® or compatible
Connections : output 3 pin XLR, 5 pin XLR, usb, PowerCon® or compatible
Brand BRITEQ
EANCode 5420025660297

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.