

BT-THEATRE 100MZ

Šifra: 15792

Kategorija proizvoda: TV i Pozorišna Rasveta

Proizvođač: BRITEQ

Cena: 71.880,00 rsd



Powerful 100W LED theater Fresnel with CCT= 3000K

The light output can be easily compared to that of traditional 1kW halogen theatre projectors!

Exceptional photometric / price performance: CRI / Ra >96, TLCl >97, CQS >94, Rf >92, Rg >97 !

Manual beam angle adjustment: 15° ~ 45° (field angle: 22° ~ 60°)

Color frame for use of color filters and eight-leaf barn door included.

No more heavy and expensive dimmer packs needed!

Very silent operation: temperature controlled, low noise cooling fan.

LCD-display to navigate easily through the setup menu!

Manual or DMX-controlled: 4 different channel modes (8bit & 16bit dimming) for maximum flexibility.

Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE ! (Briteq® code: B04645)

Flicker free TV-recordings thanks to 1.2kHz LED refresh rate!

Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.

Selectable lamp behavior: halogen lamp (slow) or led (fast).

Four dimmer curves: linear, square, inverse square, S-curve.

In case of DMX failure, you can choose between manual, blackout and freeze mode.

RDM-functionality for easy remote setup & monitoring: DMX addressing, channel mode, temperature, ...

Lock function to avoid unwanted altering of the settings.

Default factory settings + user settings can be saved/loaded.

3 & 5pin DMX in/outputs + ProLock in/outputs for easy daisy chaining.

General : Dimensions (cm) See drawing

General : Weight (kg) 7.2

General : Powerinput AC 100 - 240V, 50/60Hz

General : Energy Label No

General : Power consumption W 105

General : Color black

General : Display LCD

General : Fixation M12

General : IP rating indoor

Control : Modes standalone fixed, manual, DMX

Control : Protocol DMX, Wireless DMX, RDM

Control : programmable No

Control : upgradable software Yes

Control : minimum DMX channels 1

Control : maximum DMX channels 4

Light : lamp socket No

Light : Lux 2630 (@ 5m beam 16°)

Light : lamp COB

Light : min. color temperature (K) 3000

Light : max. color temperature (K) 3000

Light : CRI 95

Light : colors White, Warm white

Light : mix colors No

Light : functions manual focus, manual zoom

Light : min. beam angle (°) 15

Light : max. beam angle (°) 45

Light : max. refresh rate (kHz) 1.2

Connections : input 3 pin XLR, 5 pin XLR, wireless DMX optional, usb, PowerCon® or compatible

Connections : output 3 pin XLR, 5 pin XLR, usb, PowerCon® or compatible

Brand BRITEQ

EANCode 5420025660297