

Polk Audio MXT70 Black Podnostojeći Zvučnik

Šifra: 15804
Kategorija proizvoda: Podnostojeći Zvučnici
Proizvođač: Polk audio

Cena: 29.880,00 rsd



MXT70: Monitor XT Series High-Resolution Floor-Standing Loudspeaker
Hi-Res Audio Certified, Dolby Atmos, DTS:X and Auro 3D Compatible
Dual 6.5" Dynamically Balanced Woofers for Impactful Bass, Low Distortion, Better Linearity, and Increased Dynamic Range
Dual 8" Passive Radiators for Deep Effortless Bass Below 35Hz
1" Terylene Tweeter for Crystal Clear Highs Up to 40kHz
Lifelike, Detailed Imaging and Immersive Soundstage
High Sensitivity to Work with 4- and 8-Ohm Amps/Receivers
Low-Resonance Cabinet and Removable, Precision-Fit Grille
Optional: Add Monitor XT90 Height Speaker for Dolby Atmos and DTS:X Systems

Hi-Res Audio Certified

Monitor XT70's Terylene dome tweeters enable playback beyond the range of human hearing - up to 40kHz - ensuring an airy, clear, high-end energy and spaciousness that you'll not only hear but feel. MXT70 is perfect for enjoying high resolution movies, gaming or the latest hi-res streaming services like Apple Music, Tidal, Amazon Music HD, Qobuz and Spotify HiFi.

Effortless Bass

MXT70's dual Dynamically Balanced 6.5" woofers pair with two 8" passive bass radiators to play loud, low and deep, delivering Polk's famously smooth mid-range and powerful, effortless bass.

Built For Pure Listening

Monitor XT70 was made for the enjoyment of pure sound: Dual nickel-plated binding posts guarantee a direct, lossless connection and provide the ability to bi-amp the speakers; low-resonance, critically braced MDF cabinets isolate the sound of the woofers and tweeter without adding unwanted resonances; and their removable, precision-fit grilles minimize sonic interference.

Dolby Atmos and DTS:X Compatible

Compatible with the latest Dolby Atmos and DTS:X surround sound enabled AV receivers and 4- and 8-ohm amplifiers, Monitor XT does not require specialized equipment to deliver great sound. Add the MXT90 Height Speaker (available separately) to add new dimensions to your surround sound environment.

Qty Included	1
Width	9.25" (23.5 cm)
Height	40.4" (102.6 cm)
Depth	12.5" (31.8 cm)
Weight	35 lbs (15.88 kg)
Front Array Driver Complement	<ul style="list-style-type: none">• (1) 1" (2.54 cm) Terylene Dome Tweeter• (2) 6.5" (16.51 cm) Bi-laminate Paper Woofer• (2) 8" (20.32 cm) Passive Bass Radiators
Sensitivity (1 watt @ 1 meter)	89 dB
Crossover Frequency	2,700 Hz
Total Frequency Response	35 Hz → 40,000 Hz

Impedance	Compatible with 4- and 8-ohm outputs
Recommended Amplifier Power Per Channel	25 watts → 200 watts
Speaker Inputs	5-way nickel plated binding posts