

TASCAM US-1X2HR - Zvučna kartica

Šifra: 15833
Kategorija proizvoda: USB Zvučne kartice
Proizvođač: TASCAM

Cena: 9.480,00 rsd

support

US-1x2HRUS-1x2HRUltra-HDDA

High resolution reproduction in the US-HR series has been pursued based on TASCAM's policy to recreate sound as close to the original as possible. Therefore, the in-house developed Ultra HDDA mic preamp combined with a newly improved audio circuit delivers enhanced audio performance with the most transparent and low-noise sound.

Zero-latency direct monitoring function

Direct monitoring will diverge signals before sending them to the computer, resulting in smooth, in-time monitoring without any sound delay during both recording and performance.

Create quality content with bundled software

The US-HR models come bundled with world-renowned software that will enhance the user's production workflow. At the core of music production, Steinberg's Cubase LE/Cubasis LE 3 DAW is included, along IK Multimedia's Sample Tank SE, which comes free of charge with a massive 30 GB sound library encompassing more than 2,000 different musical instruments.

US-1x2HR

US-HR models also come with a free 3-month subscription to Auto-Tune Unlimited, a comprehensive suite of industry standard pitch correction and vocal effects.

Interface for podcasts and live streaming

The US-1x2HR can be used with computers or smartphones to easily create podcasts or live streams. The audio can be switched between stereo/mono, and the loopback function allows the audio from the computer to be returned to the streaming software for playback during live streams. US-1x2HR also supports OBS, which is popular and used worldwide.

Compatible with iPad and other iOS devices

The US-1x2HR can be used as an interface for iPad and other iOS devices.

New audio interface engine

Capitalizing on our experience being one of the pioneers in manufacturing USB audio interfaces, we achieved further stability in our native driver. The audio buffer size can be set starting from 4 samples (Windows only) to give the best performance to every different environment; maximizing the capability of

TASCAM US-1X2HR - Zvučna kartica

(1 mic / 1 line) / powered by USB bus power

US-1x2HRUS-1x2HR

Equipped with two inputs (1 mic / 1 line) and one USB-C port for USB bus power connection.

Natural, crisp & clear sound quality thanks to the implemented Ultra HDDA Mic Preamp with 192 kHz

Two
inputs

the computer in use while creating a low-latency environment.

Robust metal casing

The US-HR models share a solid and practical design intended to withstand long hours of hard use. Its robust metal jacket not only improves its durability but, combined with dye-cast aluminum side panels, provides a sleek, eye-catching design. In addition, all models have just the right weight, so they won't move when cables are connected or disconnected.

Features at a glance

2-in/2-out USB audio interface

Supports up to 24-bit/192 kHz audio formats

Improved TASCAM driver with selectable buffer size from 4 samples provides low-latency and stability (Windows: TASCAM native driver)

1 XLR input equipped with Ultra HDDA mic preamp and +48V phantom power

1 TRS line/inst. input

RCA line L/R inputs

RCA line L/R outputs

1 headphone output

USB Type-C connection (USB Type-A to Type-C cable included)

Powered by USB bus power

Zero-latency direct monitoring

Compatible with iPad and other iOS devices

Extensive line-up of bundled software

Steinberg Cubase LE, Cubasis LE 3

IK Multimedia Sample Tank 4 SE

Antares AUTO-TUNE UNLIMITED (available free of charge up to 3 months)

Compatible with mainstream DAW software (Pro Tools, Live, Cubase, Studio One, GarageBand, Logic Pro)

Stereo/mono selectable loopback function (Windows, Mac, iOS, iPad OS)

OBS support

Included items

US-1x2HR

USB cable (Type-A to Type-C)

DAW software installation guide

DAW plug-in software installation guide set

Owner's manual□warranty card included)

Spec description

Sampling frequency	44.1k/48k/88.2k/96k/176.4k/192k Hz
Quantization bit rate	24bit
Analog audio inputs	
MIC IN (IN 1)	
Connector	XLR-3-31(1:GND, 2:HOT, 3:COLD), BALANCED
Input impedance	2.Ꞁk ohms
Maximum input level (GAIN:MIN)	+9dBu (2.183Vrms)
Gain	58dB
LINE/INST IN(IN 2)	
LINE IN	
Connector	6.3mm(1/4") TRS-jack(T:HOT, R:COLD, S:GND), BALANCED * When set to "LINE" at LINE/INST switch
Input impedance	10k ohms
Maximum input level (GAIN:MIN)	+20dBu(7.75Vrms)
Gain	45dB
INST IN	
Connector	6.3mm(1/4") TS-jack(T:HOT, S:GND), UNBALANCED * When set to "INST" at LINE/INST switch
Input impedance	1M ohms or more

Maximum input level (GAIN:MIN)	+3dBV(1.1425Vrms)
Gain	45dB
LINE L/R IN	
Connector	RCA pin-jack, UNBALANCED
Input impedance	10k ohms
Maximum input level	+6dBV(1.9953Vrms)
Analog audio outputs	
LINE OUT	
Connector	RCA pin-jack, UNBALANCED
Output impedance	100 ohms
Maximum output level	+6dBV (1.995Vrms)
PHONES	
Connector	6.3mm(1/4") stereo phone jack
Maximum output level	18mW+18mW or more (THD+N 0.1% or less, 32ohms loaded)
Output impedance	66ohms
Working impedance	16ohms to 250ohms
Control IN / OUT	
USB	
Connector	USB Type-C
Format	USB2.0 HIGH SPEED (480Mbps)
DC IN 5V	

Connector	USB Micro B type
Power	
When connected PC	USB bus powered
When connected iOS	<p>USB power adapter (that can supply 5V and a current of at least 700mA)*1 External battery pack (that can supply 5V and a current of at least 700 mA)*2</p> <p>*1 We strongly recommend using TASCAM PS-P520E AC adapter or the USB power adapter included with the iPad/iPhone. No USB power adapter is included with an iPod touch. To use it with an iPod touch, purchase a genuine Apple USB power adapter (that can supply 5V and a current of at least 700mA) separately.</p> <p>*2 We strongly recommend using a TASCAM BP-6AA external battery pack. If using another external battery pack or mobile battery, purchase one that can supply 5V and a current of at least 700mA.</p>
Power consumption	1.8W
Dimensions	146(W) × 55(H) × 120(D)mm (including protrusions)
Weight	623g
Operating temperature	5 to 35°C
Accessories	USB cable (Type-A to Type-C), Set of DAW software installation guides, Set of DAW plug-in software installation guides, Owner's Manual (including warranty)