

TASCAM US-4X4HR - Zvučna kartica

Šifra: 15834
Kategorija proizvoda: USB Zvučne kartice
Proizvođač: TASCAM

Cena: 23.880,00 rsd

vocal/guitar simultaneous recordings and multitrack recordings. The unit is also equipped with a USB-C port to be easily powered by USB bus power.

Natural, crisp & clear sound quality thanks to the implemented Ultra HDDA Mic Preamp with 192 kHz support

US-4x4HR Ultra-HDDA Ultra-HDDA

High resolution reproduction in the US-HR series has been pursued based on TASCAM's policy to recreate sound as close to the original as possible. Therefore, the in-house developed Ultra HDDA mic preamp combined with a newly improved audio circuit delivers enhanced audio performance with the most transparent and low-noise sound.

Zero-latency direct monitoring function

Direct monitoring will diverge signals before sending them to the computer, resulting in smooth, in-time monitoring without any sound delay during both recording and performance.

Create quality content with bundled software

The US-HR models come bundled with world-renowned software that will enhance the user's production workflow. At the core of music production, Steinberg's Cubase LE/Cubasis LE 3 DAW is included, along IK Multimedia's Sample Tank SE, which comes free of charge with a massive 30 GB sound library encompassing more than 2,000 different musical instruments.

US-4x4HR

US-HR models also come with a free 3-month subscription to Auto-Tune Unlimited, a comprehensive suite of industry standard pitch correction and vocal effects.

Interface for podcasts and live streaming

The US-4x4HR can be used with computers or smartphones to easily create podcasts or live streams. The audio can be switched between stereo/mono, and the loopback function allows the audio from the computer to be returned to the streaming software for playback during live streams. US-4x4HR also supports OBS, which is popular and used worldwide.

Equipped with MIDI IN/OUT

The MIDI IN/OUT terminals allow for other MIDI external devices such as keyboards, drum machines, controllers, etc. to be synchronized and controlled.

TASCAM US-4X4HR Zvučna kartica

Optimal interface for home recording with 4 mic/line input, USB bus power, and 2 headphone outputs

US-4x4HRUS-4x4HRUS-4x4HR

The US-4x4HR is equipped with 4 mic/line inputs with guitar input support on IN 1-2 plus 2 headphone outputs that can be put to use in various music/multi-media production environments such as

Compatible with iPad and other iOS devices

The US-4x4HR can be used as an interface for iPad and other iOS devices.

New audio interface engine

Capitalizing on our experience of being one of the pioneers in manufacturing USB audio interfaces, we achieved further stability in our native driver. The audio buffer size can be set starting from 4 samples (Windows only) to give the best performance to every different environment; maximizing the capability of the computer in use while creating a low-latency environment.

Robust metal casing

The US-HR models share a solid and practical design that has been applied to withstand long hours of hard use. Its robust metal jacket not only improves its durability but, combined with dye-cast aluminum side panels, provides a sleek and eye-catching design. In addition, all models have just the right weight, so they won't move when cables are connected or disconnected.

Features at a glance

4-in/4-out USB audio interface

Supports up to 24-bit/ 192kHz audio formats

Improved TASCAM driver with selectable buffer size from 4 samples provides low-latency and stability (Windows: TASCAM native driver)

4 XLR/TRS combo inputs equipped with Ultra HDDA mic preamps and +48V phantom power

Combo TRS line inputs with guitar input support on IN1-2

TRS line outputs 1-2/3-4

Two headphone outputs

Equipped with MIDI IN/OUT terminals

USB Type-C connection (USB Type-A to Type-C cable included)

Powered by USB bus power

* 48V phantom power requires PC power supply via USB-C connection.

Zero-latency direct monitoring

Compatible with iPad and other iOS devices

Extensive line-up of bundled software

Steinberg Cubase LE, Cubasis LE 3

IK Multimedia Sample Tank 4 SE

Antares AUTO-TUNE UNLIMITED (available free of charge up to 3 months)

Compatible with mainstream DAW software (Pro Tools, Live, Cubase, Studio One, GarageBand, Logic Pro)

Stereo/mono selectable loopback function (Windows, Mac, iOS, iPad OS)

OBS support

Included items

US-4x4HR

AC adapter PS-P1220E

USB cable (Type-A to Type-C)

DAW software installation guide

DAW plug-in software installation guide set

Owner's manual (warranty card included)

Spec description

Sampling frequency	44.1k/48k/88.2k/96k/176.4k/192k Hz
Quantization bit rate	24bit
Analog audio inputs	
MIC IN	IN 1 / IN 2, IN 3 / IN 4
Connector	XLR-3-31(1:GND, 2:HOT, 3:COLD), BALANCED
Input impedance	2.2k ohms
Maximum input level (GAIN:MIN)	+9dBu (2.183Vrms)
Gain	56dB
INST IN	IN 1 / IN 2
Connector	6.3mm(1/4")TS-jack(T:HOT, S:GND), UNBALANCED (When set to "INST" at MIC/LINE INST switch)
Input impedance	1M ohms or more
Maximum input level (GAIN:MIN)	+10dBV(3.162Vrms)
Gain	56dB
LINE IN	IN 1 / IN 2, IN 3 / IN 4

Connector	6.3mm(1/4")TRS-jack(T□HOT, R□COLD, S□GND), BALANCED (When set to "MIC/LINE" at MIC/LINE INST switch)
Input impedance	10k ohms
Maximum input level (GAIN:MIN)	+20dBu(7.746Vrms)
Gain	56dB
Analog audio outputs	
LINE OUT	1-2, 3-4
Connector	6.3mm(1/4")TRS-jack(T□HOT, R□COLD, S□GND), BALANCED
Output impedance	210 ohms
Nominal output level	+4dBu (1.228Vrms)
Maximum output level	+20dBu (7.746Vrms)
PHONES	
Connector	6.3mm(1/4") stereo phone jack
Maximum output level	45mW+45mW or more (THD+N 0.1% or less, 32ohms loaded)
Output impedance	51.5ohms
Working impedance	16ohms to 600ohms
MIDI IN /OUT	
Connector	Din 5-pin
Format	Standard MIDI format
USB	
Connector	USB Type-C
Format	USB2.0 HIGH SPEED (480Mbps)

Power	
When connected PC	USB bus powered AC Adapter (TASCAM PS-P1220E, included)
When connected iOS/iPadOS	AC Adapter (TASCAM PS-P1220E, included)
Power consumption	2.25W
Dimensions	296(W) × 65(H) × 160(D)mm (including protrusions)
Weight	3.53lb (1.6kg)
Operating temperature	5 to 35°C
Accessories	AC adapter(TASCAM PS-P1220E), USB cable (Type-A to Type-C), Set of DAW software installation guides, Set of DAW plug-in software installation guides, Owner's Manual (including warranty)