

CASIO LK-280

Šifra: 11641

Kategorija proizvoda: Klavijature sa Svetlećim

Dirkama

Proizvođač: CASIO



Cena: 33.480,00 rsd.

Keyboard

61 standard-size keys

Touch Response: 2 types, Off

Key Light System: Up to 10 keys can be lit at the same time

Maximum Polyphony

48 notes (24 for certain tones)

Tones

Built-in Tones: 600

Sampling: Tones Up to 8 (Melody Sampling: 5, Drum Sampling: 3*, Up to 10 seconds)

Functions: Layer, Split, Piano/Organ button

Reverb

1 to 10, Off

Chorus

1 to 5, Off

Metronome

Beats per Measure: 0, 2 to 6

Tempo Range: 30 to 255

Song Bank

Built-in Songs: 152

User Songs: Up to 10*

Step Up Lesson

Lessons: 4 (Listen, Watch, Remember, Auto)

Lesson Part: L, R, LR

Functions: Repeat, Voice Fingering Guide, Note Guide, Performance Evaluation

Music Challenge

20 notes

Auto Accompaniment

Built-in Rhythms: 180

Chord Book Function

Chord guide

Recorder

Real-time recording, playback

Keyboard Play 5 songs, 6 tracks

Playing Along with a Built-in Songs: 1 song (L, R, LR)

Memory Capacity: Approximately 12,000 notes (total for 6 songs)

Other Functions

Transpose: ± 1 octaves (-12 to +12 semitones)

Octave Shift: Upper/Lower ± 2 octaves

Tuning: A4 = 415.5 to 465.9 Hz (Initial Default: 440.0 Hz)

Preset Scales: 17

Music Preset: 305

One Touch Preset: 180

Auto Harmonize: 12 types

Arpeggiator: 90 types

MIDI

16 multi-timbre received, GM Level 1 standard

Musical Information Function

Tone, Rhythm, Song Bank numbers and names, staff notation, fingering, pedal operation, tempo, measure and beat number, chord name, etc.

Memory Cards

Supported Memory Cards: SD or SDHC memory cards, 32GB or less

Functions: SMF playback, file storage, file recall, file delete, card format

Inputs/Outputs

USB port: TYPE B

Sustain/Assignable jack: Standard jack (sustain, sostenuto, soft, rhythm)

Phones/Output jack: Stereo standard jack; Output Impedance: 140Ω, Output Voltage: 4.5V (RMS) MAX

Audio In jack: Stereo standard jack

Input Impedance: 9kΩ, Input Sensitivity: 200mV

Mic In/Sampling jack: Standard jack (connect a dynamic microphone only)

Input Impedance: 3kΩ, Input Sensitivity: 10mV

Power Jack

DC9.5V

Power Supply

2-way

Batteries: 6 AA-size zinc-carbon batteries or alkaline batteries

Battery Life: Approximately 3 hours continuous operation on alkaline batteries

AC Adaptor: AD-E95100L

Auto Power Off: Approximately 6 minutes (during battery operation) or 30 minutes (during AC adaptor operation) without any operation, Auto Power Off can be disabled.

Speakers

12 cm × 2

Output:: 2,5 W + 2,5 W

Power Consumption

9,5 V = 7,7 W

Dimensions

94.8 × 35.0 × 10.3 cm (37 5/16 × 13 3/4 × 4 1/16 inch)

Weight

Approximately 4.5kg (9.9 lbs) (without batteries)