

## Warm Audio WA-CX12 - Studijski lampaški mikrofon

Šifra: 16331

Kategorija proizvoda: Lampaški Mikrofoni

Proizvođač: Warm Audio

**Cena: 119.880,00 rsd**

### Warm Audio WA-CX12 - Studijski lampaški mikrofon

Faithful Recreation of the Original AKG C12  
Warm Audio's WA-CX12 specifically recreates the original run of C12s produced by AKG in Austria from 1953 to 1963 (with less than 2500 made). Custom, Solid Brass CK12-Style Capsule  
The WA-12-B-60V dual capsule is edge-terminated and custom-machined out of solid brass. It is meticulously spec'd to match the detail and warmth of the original.  
Premium Tube and Capacitors  
Rigorously tested, hand-selected 12AY7 vacuum

tube and capacitors.

Custom TAB-Funkenwerk (AMI) USA Output Transformer

The large-core, imported German laminations drive all of the full natural sound captured by the capsule.

Smooth Highs and Vibrant Midrange

The WA-CX12 captures organic and natural sounding tones with pleasing high end and colorful midrange to capture nuanced, musical recordings.

9 Polar Patterns

Including cardioid, omnidirectional, and figure-8 patterns plus 6 intermediate stages for ultimate versatility, especially in stereo-pairs.

Boutique 7-Pin GAC-7 Tube-Microphone Cable from Gotham Switzerland

Using vintage-correct construction methods and highly upgraded components, the 16.4', 7-pin mic cable achieves near-perfect signal transfer.

Vintage Hard Carrying Case for All Components

Safely transport your mic anywhere with the custom, ultra-durable, vintage-vibe tweed carrying case.

A Studio Staple for Accurate Recordings

Solo vocalists

Piano (stereo pairs)

Room mic

Guitar and bass amp mic (close and distant)

Choral/group vocals

String sections

Microphone

Primary Applications Studio Recording

Form Factor Large Diaphragm Mic

Intended Sound Sources Vocals, Electric Guitar, Electric Bass, Piano, Instrument, Strings, Choir, Room Ambiance

Sound Field Mono

Capsule 2 x Condenser

Polar Pattern Cardioid, Figure-8, Multi-Directional, Omnidirectional

Pattern Selection Switched (Adjustable on Power Supply)

Orientation Side Address

Circuitry Tube (12AX7/ECC83)

Performance

Frequency Range 30 Hz to 20 kHz

Maximum SPL 149 dB SPL

Impedance 200 Ohms

Signal-to-Noise Ratio 73 dB

Equivalent Noise Level 32 dB A-Weighted

Connectivity

Output Connectors (Analog) 1 x XLR 3-Pin Male (on Power Supply)

Cable Length 16.4' / 5 m  
Number of Conductors 7  
Physical  
Color Silver  
Mounting Shockmount (Included)  
Mounting Thread Size 5/8"-27 Female  
Included Case Hard Case  
Construction Material Brass  
Dimensions ø: 2 x L: 11.6" / ø: 5 x L: 29.5 cm  
Weight 2.43 lb / 1.1 kg (Microphone)  
17 lb / 7.7 kg (Cable, Power Supply, with Mount)