Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Warm Audio WA-84 Nickel Stereo Pair - Studijski mikrofon



Šifra: 16334
Kategorija prozivoda: Sa Malom Dijafragmom
Proizvođač: Warm Audio

Cena: 77.880,00 rsd

Each WA-84 features a CineMag USA transformer in its signal path to warm up and enlarge the sound source. Also, included are audiophile components including polystyrene and Wima capacitors and a Fairchild FET, which provide a gorgeous sounding circuit with great signal integrity and a smooth boutique tone, resulting in a creamy-smooth top end and a beefy mid-to-bottom.

Each microphone's cardioid capsule is replaceable and is easily unscrewed from the body. The enclosure features a -10 dB pad to attenuate loud sources, while the gold-plated 3-pin XLR connector ensures a solid connection to a microphone cable (available seperately). The WA-84 offers a frequency response of 20 Hz to 20 kHz and can capture sources with a maximum SPL of 133 dB (with the -10 dB pad engaged). The Warm Audio WA-84 Stereo Pair includes two shockmounts, two microphone clips, two windscreens, and a carrying case.

Stereo pair of vintage-style small condenser microphones
Each mic utilizes a CineMag USA transformer
+48V phantom powered
Frequency Range: 20 Hz to 20 kHz
Pad: 0 dB or -10 dB
Maximum SPL: 123/133 dB (0/-10 dB)
Connector: 3-pin gold-plated XLR
Package Includes: Two microphones, two cardioid capsules, two shockmounts, two mic clips, two windscreens, and a carrying case

Microphone
Form Factor Stand/Boom Mount
Sound Field Mono
Operating Principle Pressure Gradient
Capsule Condenser
Polar Pattern Cardioid
Orientation End Address
Circuitry Solid-State
Pad -10 dB
High-Pass Filter None
Tone Adjustment None
On-Board Controls Pad
Windscreen Foam (Included)
Performance
Frequency Range 20 Hz to 20 kHz

Maximum SPL 133 dB SPL
Impedance 200 Ohms
Load Impedance 1 Kilohms
Sensitivity -39 dB at 1 kHz
Dynamic Range 107 dB A-Weighted
Signal-to-Noise Ratio 78 dB A-Weighted
Equivalent Noise Level 16 dB A-Weighted
Connectivity
Output Connectors (Analog) 1 x XLR 3-Pin Male (Locking, on Mic)
Power
Operating Voltage 48 V (Phantom Power)
Physical
Color Nickel
Mounting Mic Clip/Stand Adapter, Shockmount (Included)
Construction Material Metal
Dimensions ø: 0.87 x L: 5.2" / ø: 22 x L: 132 mm
Weight 4.3 oz / 122 g
Packaging Info
Package Weight 4.445 lb
Box Dimensions (LxWxH) 13.6 x 11.2 x 4"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.