
Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Vertere Magneto MM Gramofonska Glava



Šifra: 16422
Kategorija prozivoda: Igle i Glave
Proizvođač: Vertere

Cena: 23.880,00 rsd

Magneto
A high-specification Dual Moving Magnet Phono Cartridge, Magneto has been designed and manufactured by Vertere Acoustics to their exacting standards, and delivers an unparalleled musical experience in its class.

An ideal starter cartridge for new phonograph owners with a love of high-fidelity, Magneto is quiet, dynamic, accurate, easy to optimise, tolerant of records in less-than-perfect condition (which is often the case when owners return to vinyl after many years of absence), yet superbly musical, imbued with all the qualities one expects of Vertere products.

The dual magnet layout replicates the structure of the cutter head, with a V-form twin-magnet design to mimic the left & right channel sides of the record groove.

Permalloy centre shield plating provides a higher frequency response, with electrical crosstalk typically better than 40dB.

Use of laminated para-toroidal coils, along with the aforementioned "V" geometry of the magnets also gives rise to higher efficiency in generating the output signal.

Magneto utilises a finely-finished elliptical stylus to ensure outstanding tracking ability, plus super-quiet tracing of the record groove.

Magneto is closely related to the Audio Technica VM520EB cartridge (originally fitted to the DG-1) and is stylus-compatible with the AT VM5x range. This allows Magneto owners to upgrade to an improved stylus profile – if desired – when the time comes to renew.

Features
Replaceable Stylus
Integrated Stylus Guard
Stainless Steel Fixing Bolts, Washer & Hex Thumb Nuts
Easy Alignment-Assist Markings

Specifications
Frequency Response: 20 – 23,000Hz
Channel Separation: 27dB (1kHz)
Output Channel Balance: 1.5dB (1kHz)

Output Voltage: 4.5mV (1kHz, 5cm/sec.)
Vertical Tracking Angle: 23 °
Vertical Tracking Force Range: 1.8 – 2.2g (2.0g standard)
Stylus Shape: Elliptical Bonded
Stylus Size: 0.3 x 0.7 mil
Stylus Construction: Bonded Round Shank
Cantilever: Aluminium Tube
Coil Impedance: 2,700 Ohm (1kHz)
Static Compliance: 35 x 10-6 cm/dyne
Dynamic Compliance: 8 x 10-6 cm/dyne (100Hz)
Recommended Load Impedance: 47,000 Ohm
Recommended Load Capacitance: 100 – 200pF
Weight: 6.4g
Dimensions: 17.3 (H) x 17.0 (W) x 28.2 (L) mm

Weight	0.064 kg
Dimensions	2.82 × 1.7 × 1.73 cm
Colour	Black / White / Orange

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.