logo not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

GHQRD: Anni Black Integrisano Pojačalo

CHORD Anni Black Integrisano Pojačalo

Šifra: 16425

Kategorija prozivoda: Integrisana Pojačala

Proizvođač: Chord Electronics

Cena: 167.880,00 rsd

Anni is our first-ever desktop integrated amplifier. Capable of driving both headphones and compact loudspeakers, Anni benefits from the company's proprietary ULTIMA circuit topology and is perfectly positioned to exploit the full potential of today's high-performance headphones, desktop monitors and high-resolution audio sources.

The new Anni desktop integrated amplifier forms part of the Qutest range and seamlessly complements the resolving abilities of the multi-award-winning Qutest standalone DAC and Huei phono stage. As a system, the Qutest components provide an unrivalled desktop audio solution, offering class-leading digital and analogue technologies for the modern music lover. The company's compact QSS (Qutest Stand System) modular equipment rack provides the perfect support, too.

Anni offers the recently announced dual-feed-forward error-correction circuit topology whether using headphones or compact loudspeakers. Anni's advanced technology allows it to drive any headphone load, error-monitored and compensated amplification at all times.

Benefitting from both 3.5 mm headphone outputs and ¼-inch (6.35 mm) outputs, so two can listen simultaneously, plus 4 mm banana-type loudspeaker outputs, Anni delivers 10 watts of quality ULTIMA amplification, controlled by a fascia-mounted volume control that also doubles as an input selector switch for Anni's two line-level inputs. A two-stage gain control for loudspeakers provides additional flexibility with a wide range of desktop monitors.

Next-generation Dual Feed Forward amp topology Powerful headphone amp with 3.5 mm and 6.35 mm outputs 4 mm (banana) loudspeaker outputs Gain control Two line inputs KEY FEATURES 10 w into $8\Omega10$ w into 8Ω

Class AB Sliding BiasClass AB Sliding Bias

HF Switch Mode Power SupplyHF Switch Mode Power Supply

Trickle down Ultima technologyTrickle down Ultima technology

Unbalanced RCA Inverted InputsUnbalanced RCA Inverted Inputs

3.5 mm and 6.35 mm headphone jack outputs 3.5 mm and 6.35 mm headphone jack outputs

4 mm (banana) loudspeaker outputs 4 mm (banana) loudspeaker outputs

Solid Aluminium ChassisSolid Aluminium Chassis

INCLUDED ACCESSORIES

Anni Manual Safety instructions

1.5 m 15 V 6 A switch-mode power supply

Power Output: 10 W 8 ohms

THD: 0.02%

Signal to Noise: -92 dB Noise floor: -110 dB

Frequency response: 5 Hz - 60 Khz (-3 dB)

Dimensions: 160 mm (W) x 42.50 (H) mm x 96.60 (D) mm

Weight: 625 g