

Polk Audio R700 Black Podnostojeći Zvučnik

Šifra: 16435

Kategorija prozivoda: Podnostojeći Zvučnici

Proizvođač: Polk audio

Cena: 83.880,00 rsd

Polk Audio R700 Black Podnostojeći Zvučnik

AWARD WINNING PERFORMANCE

FLAGSHIP POLK SOUND

The Reserve Series incorporates groundbreaking Polk technologies found on our award-winning Legend Series to bring its flagship sound to more people.

SIT RIGHT EVERYWHERE

PINNACLE RING RADIATOR TWEETER

The Pinnacle Ring Radiator Tweeter's distinctive pointed shape guides the dispersion of high frequency sounds around a room. This innovation widens the sweet spot and allows you freedom to enjoy your music and movies wherever you choose to sit.

STRENGTH IN MOTION

TURBINE CONE WOOFER

Our pioneering turbine design delivers a significant increase in cone rigidity without increasing mass. This innovation means the woofer can move with increased accuracy and speed to deliver enhanced sound resolution, enabling you to experience a breathtaking level of detail in your music and movies.

CLEAN, DETAILED, EFFORTLESS BASS

POWER PORT 2.0

Polk's new Power Port 2.0 is the latest version of our successful Power Port technology. In addition to Power Port's carefully engineered port design that smooths the flow of air as it exits the cabinet through the port, X-Port adds a set of closed-pipe absorbers that are specifically tuned to unwanted cabinet and port resonances. Together, these two technologies combine to function as Power Port 2.0 to deliver smooth, detailed audio. Combined with dual 8" woofers, you'll get louder, cleaner bass while minimizing turbulence and port noise.

FORM AND FUNCTION

EXCEPTIONAL CABINETRY

Reserve's sleek cabinetry hides a world of audio innovation. Cabinets are carefully cross-braced to best eliminate unwanted interior resonances. Rounded exterior corners help disperse sound broadly around the room with minimal diffraction, creating an open sound stage.

OPTIONAL HEIGHT MODULE

For immersive vertical sound, add compatible Reserve R900 height modules (sold separately). These optional height modules perform beautifully with the latest home theater technologies, including: Dolby Atmos, DTS, DTS:X, DTS:X Virtual, IMAX Enhanced, and Auro-3D.

CERTIFIABLY EXCELLENT

HI-RES CERTIFIED, DOLBY ATMOS ENABLED & IMAX ENHANCED

Specification

Speaker Type	Floorstanding Loudspeaker
UOM (Sold As)	Each

TRANSDUCER

Tweeter	1" Pinnacle Ring Radiator
Mid-range/Mid-bass	6 ½" Turbine Cone
Woofer	Two 8" Polypropylene
Overall Frequency Response	30Hz - 50kHz
Frequency Response (-3dB limits)	38Hz - 38kHz
Recommended Amplifier Power	50 - 300W
Amplifier Output Compatibility	8Ω / 6Ω / 4Ω
Minimum Impedance (ohms)	3.6Ω

Sensitivity (2.83V/1m)	88dB
------------------------	------

CROSSOVER

Tweeter/Mid-range Crossover Frequency	2700
---------------------------------------	------

Mid-range/Mid-bass Crossover Frequency	350
--	-----

MEASUREMENTS

Product Dims W x H x D (Includes width of feet)	320.7 x 1143.8 x 428.3mm 12.6 x 45 x 16.9 in
---	--

Product Weights (each)	79.1 lbs/35.9 kg
------------------------	------------------

Shipping Weight	94.4 lbs/42.8 kg
-----------------	------------------

CABINETRY

New CRC (Mid-Range Enclosure Type)	Sealed with CRC
------------------------------------	-----------------

Mid-Bass / Woofer Enclosure Type	Floor Firing Power Port with X-Port
----------------------------------	--

Available Finishes

Black / Walnut

Feet

Spike and Pad

Wall-Mountable (keyhole slots)

No

Binding Posts: Nickel-plated 5-Way

Dual

Certifications (Non-Safety and Regulatory)

Hi-Res Certified

Yes

IMAX Certified

Yes

Shipping Dims (WxHxD)

550 x 423 x
1250mm
(21.6 x 16.7 x 49.2)
in