

CORDIAL CDMX 1 FRNC

Šifra: 9371

Kategorija proizvoda: Digitalni Kablovi

Proizvođač: Cordial

Cena: 222,00 rsd.

Mechanical data

Conductor area: 0,22 mm²

Composition of conductor: 7 x 0,20 mm Cu verzint / tinned copper

Conductor isolation: geschäumtes Spezial Polyolefin

Composition of cores: 1 verdrilltes Paar / 1 twisted pair

Pair screen / screen: Folie (PT/AL) + Beilaufnitze / foil (PT/AL) + drain wire

Overall screen: tinned copper braided screen

Overall jacket: flammwidriges Copolymer black

Overall diameter: 4,6 ± 0,2 mm

Weight: 34 g / m

Working temperatur:

mobile: (-5 °C) - (+70 °C)

fixed: (-20 C) - (+80 C)

min. Bending radius

mobile: 10x overall diameter = ~ 48 mm

fixed: 5x overall diameter = ~ 24 mm

Conductor resistance: 85Ω

Capacity (cond./cond.): 42 pF / m

Capacity (cond./screen): 90 pF / m

Attenuation: 2,49 dB (100m) 5, 47 dB (100m) 8,56 dB (100m)

Characteristic impedance: 108 109 97

Test voltage: 500 V e

/ km