Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

FOCAL TWIN 6 ST6 RED - Studijski monitor



Šifra: 16631
Kategorija prozivoda: Aktivni Studijski Monitori
Proizvođač: Focal

Cena: 191.880,00 rsd

Kabinet od medijapana sadrži dva 6.5-inčna 'sendvič' vufera 'W' konusa i berilijumski invertirani kupolasti visokotonac sa 'M' oblikovan zaštitinom rešetkom, drajvere koji unisono pružaju pun i neutralan zvuk, širokog frekventnog opsega. Fokalov patent, tehnologija TMD - Tuned Mass Damper, tu je da umanji distorziju u opsegu frekvencije od 1 do 3kHz, za čitavih 50%. **TWIN 6** ima i high-pass crossover, automatski stand-by režim (koji se može isključiti), kao i 160Hz crossover za konzolne refleksije, što ga sve zajedno čini vodećim monitorom čitave industrije.

Focus režim frekvencijskog opsega do 10 kHz daje paralelne mogućnosti: regularnog dvosmernog monitora, i jednosmernog monitora punog opsega (samo) iz vufera, kao da je u upotrebi i drugi par studijskih monitora sa redukovanom dinamikom, što daje prilagodljivost miksa za 'provere' na manjim sistemima.

KLJUČNE ODLIKE

Berilijumski invertirani kupolasti visokotonac: vrlo mala usmerljivost, odlična linearnost i dinamika

Optimizovana pregrada visokotonca: odlična kontrola disperzije

Kompozitna, 'sendvič-W' kupola: zvučna neutralnost, izostanak distorzije

Automatski *Stand-by* režim, koji se može isključiti

Settings: activatable/deactivatable, LF shelving, HF shelving, LPF @ 160Hz

Monitor Type: Active 2-Way, Enclosure: Bass-Reflex, Shielded

Power Rating: 190 W RMS

Drivers - HF Driver: 1 x 1.5" / 3.8 cm Beryllium Inverted Dome Tweeter

LF Driver: 2 x 6.5" / 16.5 cm Composite Cone

Amplification: 1 x HF Amplifier: Rated at 50 W RMS, 2 x LF Amplifier: Rated at 70 W RMS

Performance

Frequency Response: 45 Hz to 40 kHz ± 3 dB, Maximum Sound Pressure Level (SPL): 112 dB

Analog Input Sensitivity/Gain: +4 dBu / -10 dBV (Fixed), Phase Adjustment: None

Protections and Limiting: Fuse

Signal Processing

EQ - 1 x Low-Mid Shelf: -3 to +3 dB at 250 Hz (Continuously Variable dB Increments)

1 x Mid Notch/Peak: -3 to +3 dB at 160 Hz (Continuously Variable dB Increments)

1 x HF Shelf: -3 to +3 dB at 4.5 kHz (Continuously Variable dB Increments)

Filters - 1 x High-Pass at 45 to 90 Hz

Parametric EQ: None

Connectivity

Audio I/O - 1 x XLR Balanced Analog Input (10 Kilohms)

Power

AC Input Power 100 to 240 VAC, 50/60 Hz

General

Enclosure Material: MDF

Dimensions: 51.4 x 25.8 x 34.4 cm

Weight: 22.0 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.