

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN AUDIO VIA2502 - Razglasno pojačalo

Šifra: 16686
Kategorija proizvoda: Razglasna Pojačala
Proizvođač: Martin Audio

Cena: 311.880,00 rsd

Small to medium-scale installations
Portable sound and stage monitoring
Hotels, restaurants and bars
Houses of Worship and auditoriums
Educational facilities
Live music and dance clubs
Mobile DJ's

Its high efficiency design reduces the energy drawn from the mains supply and ensures the power reserves needed to deliver superb sound in demanding environments with reliability and ease.

Comprehensive protection functions continuously monitor its performance to maintain safe operating conditions and full output capability in ambient temperatures up to 40°C.

For a wide variety of installations and portable situations, the VIA2502 is ideally partnered with the Martin Audio DX0.5 system processor. Larger installations will benefit from use with the DX4.0 processor with its onboard network capability and proprietary VU-NET software control.

GENERAL

TYPE Two-channel Class D amplifier

POWER OUTPUT *

2 x 1250W into 2 ohms

2 x 800W into 4 ohms

2 x 450W into 8 ohms

1 x 2500W bridged into 4 ohms

COOLING Vari-speed fans, front-to-back airflow

MAXIMUM AMBIENT TEMPERATURE 40°C (105°F)

AUDIO INPUTS/OUTPUTS

ANALOGUE IN/LINK (4 CHANNELS) 2 x female, 2 x male Neutrik™ XLR

ANALOGUE INPUT IMPEDANCE 10kΩ Balanced

MAXIMUM ANALOGUE INPUT LEVEL +20dBu

AMPLIFIER OUTPUTS 2 x Neutrik Speakon™ NL4

AUDIO PERFORMANCE

OUTPUT NOISE -113dBA, referenced to max output
(22kHz bandwidth)

FREQUENCY RESPONSE <10Hz ->20kHz +/- 0.25dB

TOTAL HARMONIC DISTORTION 0.003% typical, 1kHz @ 1W

SLEW RATE > 80V per microsecond

MARTIN AUDIO VIA2502 - Razglasno pojačalo

Features

Two channels of efficient Class D amplification

2500 Watts total power output

2U rack height

Exceptionally lightweight

Switch mode power supply

Variable speed cooling fan with front-to-back airflow

Global mains operation, 115V to 230V auto-sensing

Comprehensive protection systems

Signal and clip limiter LEDs

Applications

DAMPING FACTOR 120 ref 8 ohms

POWER SUPPLY

TYPE High current, high frequency switch-mode

AC OPERATING RANGE 100-240V +/-10%

45 - 65Hz

TOTAL SYSTEM EFFICIENCY > 90% typical

MAINS CONNECTOR 1 x Neutrik Powercon™

PHYSICAL

DIMENSIONS

(W) 482 x (H) 2U/88mm x (D) 441mm

(W) 19in x (H) 2U/3.5in x (D) 17.4in

incl handles and optional rear support

WEIGHT 8kg (17.6lbs)