Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

FBT X-LITE 110A - Aktivni zvučnik



Šifra: 16800
Kategorija prozivoda: Aktivne Zvučne Kutije
Proizvođač: FBT

Cena: 59.880,00 rsd

PRODUCT DESCRIPTION
The FBT XLITE 110A series speakers with integrated 3-channels mixer feature lightweight, yet rugged gas injected molded polypropylene cabinet construction. Available in black finish, the FBT XLITE 110A series speakers provide fixed installations with an elegant design that blends into any decor.

The asymmetrical shape of the FBT XLITE 110A cabinet also allows use as a powered floor stage monitor.

The FBT XLITE 110A is two way design incorporating a 10” low frequency woofer and 1” HF compression driver coupled to a 90°H x 60°V constant directivity horn. With a frequency range of 58Hz - 20kHz the FBT XLITE 110A speaker provide high fidelity sound for both speech and music applications with a maximum SPL of 127dB.

The bi-amplified FBT XLITE 110A active speaker feature a 1200W low frequency amp and a 300W high frequency amp. The control panel features a three-channel mixer with two micro-line inputs, a stereo input and a dedicated channel for bluetooth 5.0; two XLR inputs, stereo input, XLR output with ch1 or mix link selector, HP filter, two mic-line selectors, DSP preset selector, Bluetooth 5.0 with pairing led. 4 x M10 rigging points built-in into the cabinet along with the optional mounting brackets allow the FBT XLITE 110A speaker to be surface mounted on walls or ceilings.

A standard 35mm speaker stand socket allows the FBT XLITE 110A to be mounted on speaker stand
KEY FEATURES
2 way bi-amplified bass reflex system
Polypropylene moulded enclosure
Custom 10" woofer (LF) / 2.5" voice coil
1" throat / 1.4" voice coil HF compression driver
1200w / 300w Built-In amplifier (LF / HF)
Bluetooth 5.0
3-Channel mixer
4 DSP Presets
30 degrees & 45 degrees monitor tapers
Universal switch mode power supply 100-240 VAC
M10 rigging points

SPECIFICATIONS
Configuration: 2 Way
Frequency response: 58Hz - 20KHz
Low frequency woofer: 10" - 2.5" VC
High frequency driver: 1" - 1.4" VC

Maximum SPL cont/peak: 123/127 dB
Dispersion: 90 x 60
Input impedance: 22
Input connector: XLR IN/OUT
Net Dimension (WxHxD): 300 x 536 x 301.5
Net Weight: 13 KG
Transport Dimension (WxHxD): 370 x 615 x 380
Transport Weight: 14.8 KG
Built in amplifier peak: LF 1200w HF 300w

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.