Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

BAREFOOT Footprint01 Studijski monitor



Šifra: 16807
Kategorija prozivoda: Aktivni Studijski Monitori
Proizvođač: BAREFOOT

Cena: 551.880,00 rsd

The 2-way DSP crossover feeds dual Class D amplifier modules that drive the subwoofers with 500W of power and deliver 150W to the mid- and high-frequency drivers. There is a passive crossover network between the midrange driver and the tweeter. The midrange woofer is positioned above the tweeter in an unusual speaker geometry that creates the acoustic focus in the center of the cabinet.

Barefoot’s approach to reference monitor speaker design has always been to provide audio professionals with exemplary sound quality, wide dynamic range and bass extension at every stage of the audio production process, from recording through mixing to mastering. But not every project begins or ends in a high-end studio that offers Barefoot MicroMain or MasterStack monitors. The new Footprint01 model is Barefoot Sound’s response to evolving modern workflows, making the company’s ultra-high performance technologies available to audio professionals working in home-based facilities, smaller writing, editing or post production rooms, or on the road. Now, composers, songwriters, musicians, beat-makers, post production specialists and others can benefit from the Barefoot sound, whatever their work environment.

Description: 3-way active monitor with MEME™ voice emulation
Controls: Input level stepped attenuator, MEME voice select
Input Impedance: Balanced XLR, 50k Ohm Impedance
Sensitivity: 90dB @ 1 meter with -15dBV input signal (Level control set to 0dB)
Frequency Response: 36Hz – 45kHz (±3dB),
45Hz – 40kHz (±1dB)
Bass Response: -3 dB @ 36Hz, Q = 0.707
Slope = 18 dB/octave
Cabinet: 18 liters total internal volume, Sealed woofer and midrange enclosures, Machined aluminum baffle plate, Long fiber wool acoustic damping throughout
Crossover Frequencies: 250 / 3600 Hz (Passive crossover between Midrange and Tweeter)
Tweeter: 1″ ring radiator, Low distortion motor, Rear waveguide chamber
Midrange: 4.0″ aluminum cone, Aluminum phase plug, Low distortion motor, +/- 3.5 mm linear excursion
Woofers: 8″ paper cone, +/- 9.5 mm linear excursion
High Frequency Amplifier: 150W
Low Frequency Amplifier: 500W
AC Power Input: 85 VAC to 265 VAC
Power Consumption: Idle: 2W, Maximum: 765W
Weight: Speaker: 35 lbs each (16 kg)
Shipping: 44.5 lbs each (20.2 kg)
Dimensions HxWxD: Cabinet: 14.0 x 9.5 x 13.0 inches (356 x 241 x 330 mm)

Overall: 14.0 x 10.25 x 13.6 inches (356 x 260 x 345 mm)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.