Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Beyerdynamic TG H34 (TG)

Šifra: 16822
Kategorija prozivoda: Headset Mikrofoni
Proizvođač: Beyerdynamic



Cena: 5.880,00 rsd

MICROPHONE WITH MAXIMUM FREEDOM OF MOVEMENT
The TG H34 neckworn micropohone ensures maximum freedom of movement and is therefore ideal for all free-hand applications. On stage it is very popular among singing dancers, keyboarders and drummers. Furthermore, it is also suitale for all kinds of presentations and sport lessons.

NATURAL SOUND
The TG H34 features easy handling, a natural sound and optimal fit. The Supercardioid polar pattern provides a high gain before feedback. The flexible gooseneck allows optimally positioning.

TG PIN OUT
The "TG" version works on pocket transmitters from the Unite series and from the TG series, like -100, -500 or -1000. If the microphone is used wired, the "MA PVA" power converter is necessary, it converts the necessary phantom power from the microphone input into an audio wire power supply required by the microphone.

OPUS PIN OUT
The "Opus" version works with pocket transmitters from the various Opus radio series such as -300, -500, -600, -800, -900 and -910. For wired connection to a microphone input with phantom power the "CV 18" power supply is required. "Opus" and "TG" versions are electrically incompatible.

TOURING GEAR
THE BEST LIVE MICROPHONE SERIES WE'VE EVER BUILT.
Touring Gear - a series of live microphones that are set to excite performers in studios and on stages all over the world. Rugged in design with phenomenal audio quality, they are the perfect complement to beyerdynamic's legendary M series models, including well-known classics such as the M 88 and M 160.

TECHNICAL SPECIFICATIONS
Transducer type . . . . . Condenser (back electret)
Operating principle . . . . . Pressure gradient
Polar pattern . . . . . Supercardioid
Frequency response:
Close miking . . . . . 20 - 13,000 Hz
Distant miking (measured at 1 m) . . . 180 - 13,000 Hz
Open circuit voltage . . . . . 6.0 mV/Pa (-44.5 dBV)* ±3 dB
Nominal impedance . . . . . approx. 700 Ω
Load impedance. . . . . > 3.5 kΩ
Max. SPL at 1 kHz . . . . . 119 dB*
Equivalent SPL . . . . . 31.5 dB SPL*
Power supply . . . . . Direct current 1.5 - 9 V

Max. power consumption . . . . . 780 µA
Connector . . . . . Mini-XLR, 4-pin, female
Dimensions:
Diameter . . . . . 15 mm
Length microphone boom. . . . . 95 mm
Weight. . . . . 36 g

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.