Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MACKIE Onyx16 - Mikseta bez snage/Pasivna mikseta



Šifra: 16848
Kategorija prozivoda: Studijske Miksete
Proizvođač: MACKIE

Cena: 71.880,00 rsd

Onyx16 ispunjen je sjajnim sadržajima, tu su Perkins ekvilajzer u britanskom stilu, moćni DSP efekti, displej u punom koloru, kao i integrisano stereo snimanje i plejbek sa SD kartice. Mikser nudi end-to-end performanse ultra niskog šuma, koje zahteva rad studijskih profesionalaca.

Klasičan zvuk, moderne performanse

Višestruko nagrađivana Onyx pretpojačala donose do 60 dB jačine.
Premijum analogna kola isporučuju studijski kvalitet zvuka i šum drže na minimumu.

Direktno stereo (2x2) snimanje i plejbek na SD karticu

Višekanalno (24x4) snimanje u visokoj rezoluciji (96 kHz / 24-bit), za Mac/PC via USB

Direktno na SD kartu (2x2) stereo snimanje i plejbek

Četvorokanalni, dodeljivi USB return (2 stereo para)

Pošaljite vaš Main Mix na USB jednostavno, putem prekidača

Displej u punom koloru za sve studio komande, plus interfejs kontrolisan jednim potenciometrom

Jednostavna navigacija parametara efekata, onboard SD snimanje i plejbek

Vizualno pregledajte fajlove na SD kartici putem ugrađenog displeja

Dodeljivi (fizički) dugmići za komande: Previous, Next, Record, Play/Pause

Sačuvajte do 6 korisničkih preseta efekata za brz i lak odziv

Profesionalni procesor efekata visoke rezolucije

Korišćenje integrisanih efekata za lajv performanse, strimovanje i drugo.

Reverb, Delay, Chorus, itd.

Postignite savršen zvuk uz podesive parametre i dodeljive ekvilajzere

Bluetooth Streaming for Wireless Audio Streaming
Pair your Bluetooth enabled device and stream audio directly to a channel on the mixer
Streamed audio can be routed to Aux Sends and the Main Mix

Powerful Mixing Toolkit
3-band Perkins EQ with on/off hard-bypass switch on all channels
Hi-Z switches allows direct connection of guitars, basses, and other instruments
100 Hz low-cut filter and 48V phantom power on all mic channels
Stereo 3.5mm input and Bluetooth streaming
Stereo line inputs
Aux/Monitor outputs with dedicated per-channel send control
Dedicated Control Room outputs
Headphone output with dedicated level control
L/R Assign switch per channel
12-segment stereo meters
Overload indicators on all channels
PFL/AFL channel solo
Footswitch input for FX Mute (footswitch not included)
Powerful Software and Plugins
Waveform OEM recording software and plugin bundle
DAW Essentials Bundle for Waveform OEM, with 16 powerful plugins like Equalizer, Compressor, Reverber8, and Limiter
Rugged Chassis and Professional Design
Backlit mute and solo buttons provide a positive tactile feel and clear visual feedback

Mackie ONYX16 Specs
Mixer
Number of Analog Input Channels: 18 (8 Mono / 5 Stereo)
Number of Mic Preamps: 12
Analog Output Channels: 2 x Stereo Master Output
2 x Stereo Control Room/Monitor Output
2 x Mono Aux Send Output
1 x Mono FX Send Output
1 x Stereo Headphone Output
Mix Routing: 1 x Stereo Main Mix per Mono Input Channel, Stereo Input Channel, Aux Bus/Subgroup
Faders: 13 x 2.4" / 60 mm Channel Fader
1 x 2.4" / 60 mm FX Fader
2 x 2.4" / 60 mm Bus/Subgroup Fader
1 x 2.4" / 60 mm Master Fader
Meters Main Meter:
2 x 12-Segment LED
Meter Range: -30 dB to +20 dB Peak/Clip
Gain/Trim Range: +60 dB
Dynamic Processing: None
EQ: 3-Band Semi-Parametric
3-Band Shelving/Notch/Peak
EQ Parameters Mono Channels:
High: ±15 dB at 12 kHz
Mid: ±15 dB at 100 Hz to 8 kHz
Low: ±15 dB at 80 Hz
Stereo Channels:

High: ±15 dB at 12 kHz
Mid: ±15 dB at 2.5 kHz
Low: ±15 dB at 80 Hz
Filters Input Channels:
1 x High-Pass: 100 Hz
Solo/Mute Solo per Input Channel
Mute per Input Channel, Bus, FX Bus, Master
Built-In Effects: Yes
Sample Rates: 96 kHz
Bit Depth: 24-Bit
Connectivity
Analog Inputs: 12 x XLR 3-Pin Balanced Mic Input
8 x 1/4" TRS Balanced/Unbalanced Line Input
4 x 1/4" TRS Unbalanced Line Insert
2 x 1/4" TRS Balanced/Unbalanced Hi-Z Input
10 x 1/4" TRS Balanced/Unbalanced Stereo Line Input (4 Stereo Pairs)
1 x 1/4" TRS Footswitch Input
Analog Outputs: 2 x XLR 3-Pin Balanced Stereo Main Output (1 Stereo Pair)
2 x 1/4" TRS Balanced/Unbalanced Stereo Main Output (1 Stereo Pair)
2 x 1/4" TRS Balanced/Unbalanced Stereo Monitor Output (1 Stereo Pair)
2 x 1/4" TRS Balanced/Unbalanced Mono Aux/Monitor Output
1 x 1/4" TRS Balanced/Unbalanced FX Send
Phantom Power: +48 V (Applied to All Inputs)
Digital I/O: None
MIDI I/O: None
USB: 1 x USB-B (Audio Playback, Host Connection, Recording)
Recording
Max Multitrack Recording: 18 Tracks
Media Support: SD
OS Compatibility: macOS
Windows
*As of April, 2022: Check with manufacturer for the most up-to-date compatibility
Power
AC Input Power: 100 to 240 VAC, 50 / 60 Hz
AC Power Connector: 1 x IEC Input
Power Consumption: 45 W
Physical
Rack Mountable: Yes
Dimensions: 475 x 355.6 x 114.3 mm
Weight: 6.9 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.