Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MACKIE Onyx24 - Mikseta bez snage/Pasivna mikseta



Šifra: 16849
Kategorija prozivoda: Studijske Miksete
Proizvođač: MACKIE

Cena: 94.680,00 rsd

Onyx24 ispunjen je sjajnim sadržajima, tu su Perkins ekvilajzer u britanskom stilu, moćni DSP efekti, displej u punom koloru, kao i integrisano stereo snimanje i plejbek sa SD kartice. Mikser nudi end-to-end performanse ultra niskog šuma, koje zahteva rad pravih profesionalaca u studiju.

Klasičan zvuk, moderne performanse

Višestruko nagrađivana Onyx pretpojačala donose do 60 dB jačine.
Premijum analogna kola isporučuju studijski kvalitet zvuka i šum drže na minimumu.

Snimajte i slušajte putem SD kartice ili USB-a

Višekanalno (24x4) snimanje u visokoj rezoluciji (96 kHz / 24-bit), za Mac/PC via USB

Direktno na SD kartu (2x2) stereo snimanje i plejbek

Četvorokanalni, dodeljivi USB return (2 stereo para)

Pošaljite vaš Main Mix na USB jednostavno, putem prekidača

Displej u punom koloru za sve studio komande, plus interfejs kontrolisan jednim potenciometrom

Jednostavna navigacija parametara efekata, onboard SD snimanje i plejbek

Vizualno pregledajte fajlove na SD kartici putem ugrađenog displeja

Dodeljivi (fizički) dugmići za komande: Previous, Next, Record, Play/Pause

Sačuvajte do 6 korisničkih preseta efekata za brz i lak odziv

Professional High-Resolution FX Processor
Utilize built-in effects for live performances, streams, and beyond

Reverb, delay, chorus, and more
Dial in the perfect sound with adjustable parameters and dedicated EQ
Built-in effects presets provide that finishing touch out of the box

Bluetooth Streaming for Wireless Audio Streaming
Pair your Bluetooth enabled device and stream audio directly to a channel on the mixer
Streamed audio can be routed to Aux Sends and the Main Mix
Powerful Mixing Toolkit
3-band Perkins EQ with on/off hard-bypass switch on all channels
Hi-Z switch allows direct connection of guitars, basses, and other instruments
100 Hz low-cut filter and 48V phantom power on all mic channels
Stereo 3.5mm input and Bluetooth streaming
Stereo line inputs
Aux/Monitor outputs with dedicated per-channel send control
Dedicated Control Room outputs
Headphone output with dedicated level control
L/R Assign switch per channel
12-segment stereo meters
Overload indicators on all channels
PFL/AFL channel solo
Footswitch input for FX Mute (footswitch not included)
Powerful Software and Plug-Ins
Waveform OEM recording software and plug-in bundle
DAW Essentials Bundle for Waveform OEM, with 16 powerful plug-ins like Equalizer, Compressor, Reverber8, and Limiter

Mackie ONYX24 Specs
Mixer
Number of Analog Input Channels: 24 (14 Mono / 5 Stereo)
Number of Mic Preamps: 18
Analog Output Channels: 2 x Stereo Master Output
2 x Stereo Control Room/Monitor Output
2 x Mono Aux Send Output
1 x Mono FX Send Output
1 x Stereo Headphone Output
Mix Routing: 1 x Stereo Main Mix per Mono Input Channel, Stereo Input Channel, Aux Bus/Subgroup
Faders: 19 x 2.4" / 60 mm Channel Fader
1 x 2.4" / 60 mm FX Fader
2 x 2.4" / 60 mm Bus/Subgroup Fader
1 x 2.4" / 60 mm Master Fader
Meters Main Meter:
2 x 12-Segment LED
Meter Range: -30 dB to +20 dB Peak/Clip
Built-In Amplifier
Gain/Trim Range: +60 dB
Input Pad: None
Input Polarity: None
Dynamic Processing: None
Sidechain Filters: None
EQ 3-Band: Semi-Parametric (Mono Channels)
3-Band Shelving/Notch/Peak (Stereo Channels)
EQ Parameters Mono Channels:
High: ±15 dB at 12 kHz
Mid: ±15 dB at 100 Hz to 8 kHz
Low: ±15 dB at 80 Hz

Stereo Channels:
High: ±15 dB at 12 kHz
Mid: ±15 dB at 2.5 kHz
Low: ±15 dB at 80 Hz
Filters Input Channels:
1 x High-Pass: 100 Hz
Solo/Mute Solo per Input Channel
Mute per Input Channel, Bus, FX Bus, Master
Channel Output/Source Monitoring None
Built-In Effects: None
Digital Audio
Sample Rates: 96 kHz
Connectivity
Analog Inputs: 18 x XLR 3-Pin Balanced Mic Input
14 x 1/4" TRS Balanced/Unbalanced Line Input
4 x 1/4" TRS Unbalanced Line Insert
2 x 1/4" TRS Balanced/Unbalanced Hi-Z Input
10 x 1/4" TRS Balanced/Unbalanced Stereo Line Input (4 Stereo Pairs)
1 x 1/4" TRS Footswitch Input
Analog Outputs: 2 x XLR 3-Pin Balanced Stereo Main Output (1 Stereo Pair)
2 x 1/4" TRS Balanced/Unbalanced Stereo Main Output (1 Stereo Pair)
2 x 1/4" TRS Balanced/Unbalanced Stereo Monitor Output (1 Stereo Pair)
2 x 1/4" TRS Balanced/Unbalanced Mono Aux/Monitor Output
1 x 1/4" TRS Balanced/Unbalanced FX Send
Phantom Power: +48 V (Applied to All Inputs)
USB: 1 x USB-B (Audio Playback, Host Connection, Recording)
Recording
Max Multitrack Recording: 24 Tracks
Media Support: SD
Power
AC Power Connector: 1 x IEC Input
Power Consumption: 55 W
Physical
Rack Mountable: No
Dimensions: 640.1 x 355.6 x 114.3 mm
Weight: 9.8 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.