

FOCUSRITE ISA 828 MKII - Pretpojačalo

Šifra: 16890

Kategorija proizvoda: Studijska Pretpojačala

Proizvođač: Focusrite

Cena: **359.880,00** rsd

The preamp makes use of a Lundahl LL1538 input transformer to give you the sound of the original classic Focusrite preamps. Just press the ISA 110 switch to activate that vintage sound. The microphone input stage provides a variable impedance circuit. The gain range is a very healthy 80 dB, making the unit suitable for use with low-output dynamic and ribbon microphones.

Channels one through four include DI inputs that feature high- and low-impedance options, delivering a comprehensive and accessible DI solution for electric guitars and basses. Pair the device with the separately available ISA ADN8, and you'll have a great front end, one that works equally well in studios and complicated live-sound settings.

Eight-channel microphone preamp featuring original ISA transformer-based preamps

Each channel can accept either microphone or line input

Channels 1 through 4 also accept instrument inputs for guitars and basses, or vintage synthesizers with high impedance outputs

Microphone input can deliver up to 80dB of gain, particularly useful when working with very low output dynamic and ribbon microphones

Phantom power, ISA 110, and phase switches provided on each input

High-pass filter on each channel provides a 75 Hz corner frequency with 18 dB/octave roll-off

Variable microphone impedance

Six-LED input meter per channel

Separately available eight-channel analog-to-digital converter card provides eight channels A/D conversion over Dante, ADAT, or AES3, at sample rates and resolutions up to 192 kHz / 24-bit

Includes Brainworx bx_console Focusrite, a plug-in that faithfully captures the sound, feel, and style of the original Focusrite ISA 110 Equaliser and ISA 130 Dynamics Modules

Focusrite ISA828 MKII Specs

Connections 8 x XLR Mic Inputs

8 x 1/4" Line Inputs

4 x 1/4" Instrument Inputs

1 x DB25 / ADC Inputs

1 x DB25 / Analog Outputs

High Pass Filter Fixed at 75 Hz, 18 dB/Octave Rolloff

Meters 6-Segment LED Peak-Level Meters per Channel

Gain Range 80 dB

Dimensions 3.5 x 19.0 x 12.8" / 8.8 x 49.2 x 32.5 cm

Weight 15.6 lb / 7.1 kg (Without Accessories)

16.5 lb / 7.5 kg (With Accessories)

Packaging Info

Package Weight 20.04 lb

Box Dimensions (LxWxH) 22.1 x 19.6 x 6.3"