Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Pioneer XPRS1182S - Aktivni vufer



Šifra: 17084
Kategorija prozivoda: Aktivni Subwooferi
Proizvođač: Pioneer DJ

Cena: 131.880,00 rsd

The rear panel offers two combo XLR-1/4" inputs and two XLR through outputs for connecting to other speakers and subwoofers. Quick DSP adjustments are available and include three modes: Boost, Extended LF, and Normal. Additionally, there are three preset crossover settings including 80, 100, and 120 Hz. The phase switch offers a choice of 0 or 180° to prevent multiple subwoofers from cancelling each other's low frequencies. The Pioneer XPRS1182S ships with an IEC power cord.

Powerful Class-D Amplification
The XPRS2 Series employs Class-D Amplification with high output wattage for a powerful and premiere audio experience for performers and listeners alike. The XPRS1182S subwoofer offers Class-D 4000W amplification.

High Quality, Robust Build
Pioneer DJ's all-new XPRS2 Series features a sleek all-black, protective plywood cabinet for performance in harsh indoor and outdoor environments. The series models all come with a durable handle to support system portability and handling during setup and take down. The XPRS2 Series also features rubber feet to create separation and shock absorption between surfaces.

Three DSP Modes
XPRS2 subwoofers contain three different DSP preset modes: Boost, Extended LF, and Normal to suit different listening environments.
Accurate Audio Performance
The XPRS1182S employs a 18" ferrite woofer with a 3" voice coil with long excursion to produce low frequencies with paramount accuracy.

Frequency Response
As with the XPRS2 full-range speakers, the new XPRS2 subwoofers' performance is apparent through both the frequency response and maximum SPL. With the XPRS1182S providing a frequency response of 40 to 120 Hz and a maximum SPL of 130 dB, the subwoofer packs in the performance of a permanent install subwoofer with the compact mobility required by today's mobile artists, performers, and venues.

Pioneer DJ XPRS1182S Specs
Configuration Active Subwoofer
Enclosure Type Bass-Reflex Subwoofer
Total Power Capacity 4000 W Peak
2000 W Program
1000 W RMS
Amplifier Class Class-D
Drivers

MF Driver None
LF Driver 1 x 18" / 45.7 cm Woofer
LF Voice Coil 3" / 76.2 mm
Magnet Ferrite
Performance
Frequency Response 40 Hz to 120 Hz -6 dB
Maximum SPL 130 dB
Protections Short Circuit, Thermal
Connectivity
Audio I/O 2 x Combo XLR-1/4" 3-Pin Female Balanced/Unbalanced Line Input
2 x XLR 3-Pin Balanced Line Thru/Output
Network I/O None
USB None
Wireless Connectivity None
Signal Processing
Crossover 80 to 120 Hz
Dynamic Processing Compression, Peak Limiter
Phase Adjustment -180°
Digital Signal Processing Venue Settings
Power
AC Input Power 110 to 240 VAC, 50 / 60 Hz (T 10 A L 250 V)
AC Power I/O 1 x IEC Input
Power Consumption 800 W
Physical
Mounting 1 x Pole Socket (Top)
Handles 1 x Each Side
Cooling Fan (Variable Speed)
Construction Material Plywood
Dimensions 26 x 21.1 x 21" / 660.4 x 535.9 x 533.4 mm
Weight 71.2 lb / 32.3 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.