Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615 PIB: 106966344 E-mail: porudzbine@player.rs

## Pioneer XPRS122 - Aktivni zvučnik

Šifra: 17082 Kategorija prozivoda: Aktivne Zvučne Kutije Proizvođač: Pioneer DJ

# Cena: 107.880,00 rsd

Rioneert XBRS: 220e Aktivni zvučnik

#### **Powerful Class-D Amplification**

The XPRS2 Series employs Class-D amplification with high output wattage for a powerful and premiere audio experience for performers and listeners alike. The XPRS122 full-range speaker features Class-D 2000W amplification.

### **High-Quality and Robust Build**

Pioneer DJ's all-new XPRS2 Series features a sleek

all-black, protective plywood cabinet for performance in harsh indoor and outdoor environments. The series models all come with a durable handle to support system portability and handling during setup and take down. The XPRS2 Series also features rubber feet to create separation and shock absorption between surfaces.

### **Four DSP Modes**

Both of the XPRS2 full-range speakers contain four different DSP preset modes: Live, Music, Speech, and Floor Monitor to address the needs of different listening environments.

### XPRS122 Full-Range Speaker Design

The XPRS122 is the larger full-range speaker counterpart in Pioneer DJ's XPRS2 Series. Featuring a 12" woofer and 3" voice coil with a 1" exit compression driver and 1.75" voice coil, the speakers deliver comprehensive sound coverage across mid to large audiences and venues. Boasting a frequency response of 48 Hz to 20 kHz and a maximum SPL of 131 dB, the versatile full-range speaker delivers powerful sound built to thrive in even the harshest of sound environments such as a live DJ set.

### Pioneer DJ XPRS122 Specs

Configuration Active 2-Way Enclosure Type Bass-Reflex Loudspeaker Total Power Capacity 2000 W Peak 1000 W Program 500 W RMS Amplifier Class Class-D Drivers HF Driver 1 x 1" / 25.4 mm Titanium Compression Driver HF Voice Coil 1.75" / 4.45 cm LF Driver 1 x 12" / 30.5 cm Woofer LF Voice Coil 3" / 7.6 cm Performance Frequency Response 48 Hz to 20 kHz -10 dB Maximum SPL 131 dB (Peak) Protections Overload, Signal Limiter, Thermal Connectivity Audio I/O 1 x Combo XLR-1/4" 3-Pin Female Balanced/Unbalanced Mic/Line Input 1 x Combo XLR-1/4" 3-Pin Female Balanced/Unbalanced Line/Hi-Z Input 1 x 1/8" / 3.5 mm TRS Female Unbalanced Line Input 1 x XLR 3-Pin Balanced Mix Output Network I/O None **USB** None Wireless Connectivity None Signal Processing EQ None

Parametric EQ None Semi-Parametric EQ None **Filters None** Dynamic Processing Compression, Limiter Phase Adjustment None Digital Signal Processing Voicing Modes Power AC Input Power 110 to 240 VAC, 50 / 60 Hz (T 10 A L 250 V) AC Power I/O 1 x IEC Input Power Consumption 800 W Physical Mounting 1 x 1.4" / 35 mm Pole Socket (Bottom) 10 x M10 Fly Point Handles 1 x Each Side **Construction Material Plywood** Dimensions 25.1 x 14.3 x 13.8" / 637.5 x 363.2 x 350.5 mm Weight 44.5 lb / 20.2 kg