

MACKIE CR2-X Cube - Studijski monitor

Šifra: 17111
Kategorija proizvoda: Aktivni Studijski Monitori
Proizvođač: MACKIE

Cena: 20.280,00 rsd

MACKIE CR2-X Cube - Studijski monitor

Highlights

BMR driver technology for immersive room-filling sound
Capacitive-touch volume and mute controls
Compact design takes up minimal desk space
Three inputs: USB-C, 3.5mm, and Bluetooth 5.0
Subwoofer output with jack detection
Subwoofer crossover mode
Headphone output

Hearing Is Believing

Tired of small speakers that sound small? Mackie is too. They decided it was time to change that starting with the CR2-X Cube. These beauties utilize innovative BMR driver technology that delivers crystal-clear and ultrawide room-filling sound possible. Gamers that want full immersion with a level of detail that reveals every shot, footstep, and distant explosion should look no further. How about music? The CR2-X Cube speakers deliver incredible spatial accuracy and imaging, which means vocals will sound right in front of you, guitars will have depth and dimension, and everything else will claim a distinct spot in the listening area.

BMR Driver Technology

The BMR (Balanced Mode Radiator) drivers make it possible to deliver clear and immersive sound from a stealthy, compact enclosure. This innovative flat-disc design eliminates the need for a separate high-frequency driver and crossover while also removing any boxy megaphone effects common with traditional speaker cones. Despite their small size, you will experience room-filling dispersion, lifelike stereo imaging, and rich full-range sound normally reserved for much larger speakers.

Sleek Control

Along the base of the main speaker is an integrated touch bar that allows easy and elegant control over volume. And just to the right, a convenient source button allows you to quickly switch between Bluetooth 5.0, 3.5mm analog, or USB.

Mackie CR2-X Cube Specs

Speaker System
Channel Configuration 2-Channel
Speaker Configuration Full-Range
Amplifier Power Rating 60 W Peak
Drivers 1 x 3.25" / 82.55 mm Tweeter (per Speaker)
Enclosure Type Sealed
Frequency Response 58 Hz to 20 kHz (-10 dB)
Wired I/O 1 x 1/8" / 3.5 mm Output (Subwoofer)
1 x 1/8" / 3.5 mm Output (Headphone)
1 x 1/8" / 3.5 mm Input (Audio)
1 x USB-C Input (Audio)
2 x RCA Input (Audio)
2 x RCA Output (Audio)
Amplifier Class Class-D
SPL 103 dB
SNR (Signal-to-Noise Ratio) 90 dB
Controls Bluetooth Pairing, Mute, Power, Volume
Wireless Connectivity
Wireless Connection Protocols Bluetooth

Bluetooth 5.0

Power

AC Input Power 100 to 240 VAC, 50 / 60 Hz

DC Input Power 24 VDC at 2.7 A

Compatibility

Supported Sample Rates Up to 48 kHz / 16-Bit

Physical

Placement & Mounting Options Tabletop/Bookshelf

Operating Temperature 32 to 113°F / 0 to 45°C

Dimensions Each Speaker:

4.7 x 6.4 x 6" / 11.9 x 16.3 x 15.2 cm

Weight 6.3 lb / 2.9 kg