

Pro-Ject Power Box DS3 Sources Silver

Šifra: 17164
Kategorija proizvoda: Gramofoni i oprema
Proizvođač: Pro-Ject

Cena: 83.880,00 rsd



Cleanest power for ultimate sound!

It is a proven fact that a power supply is a very important part of the audio path and significantly contributes to the sonic quality of an audio product. In order to offer the possibility of improving sound quality, we designed our linear power supply Power Box DS3 Sources. It significantly enhances the sound quality of up to six Box Design components, like streamers, CD players, pre-amplifiers and also offers the possibility to connect a DC-driven turntable.

A linear power supply consists of a massive toroidal transformer with shielding between primary and secondary winding, which acts as an isolating transformer and avoids penetration of interferences from mains into the audio component. The built-in transformer has a much higher power reserve compared to the standard power adapter. It has very low output impedance and in combination with large filtration capability it can easily manage all power needs. Sound staging, darkness of silent backgrounds and small detail resolution will improve strongly and contribute to a far better overall performance of each component. Six standard connection cables are included in delivery. Special highend shielded connection cables in these lengths are available on request: 0,82m, 1.23m, 1.85m.

The following interconnect cables are supplied in box:

2 x 9V (1.3mm connector)

3 x 18V (2.5mm connector)

1 x 15V (2.1mm connector) – to connect a DC driven Pro-Ject Audio Systems turntable.*

*ATTENTION: NOT SUITABLE for the following turntables: X8, Xtension 9, Xtension 10, Xtension 12, RPM 9, RPM 10 and the models of Signature line, with high power consumption and a heavy, mass loaded, platter. For these turntables we recommend the Power Box RS2 Phono or Power Box RS Uni TT. Higher end power cables Connect it Power with superior shielding and transmission are also available for Power Box DS3 Sources!

All-in-one power supply capable of 6 components
 Cleanest power using non-switching power supply
 5 Box Design component & 1 turntable power output
 Not suitable for integrated & power amplifiers
 Soft-start-system: no current-inrush
 Audio type toroidal transformer
 Main isolating transformer with copper foil shielding
 Voltage rectification with precise regulation
 High filtration capacity (10.000 μ F)
 Low ESR capacitors
 Low noise components with surge protection
 Rigid aluminium casing protects against interference
 Available in black or silver
 Magnetic wooden side panels available separately
 Made in Europe

Input power:	115V/230V AC
Output voltage / current (socket diameter):	2 x 9V / 2A max (1,3mm)
	3 x 18V / 1A max (2.5mm)
	1 x 15V / DC-turntable (2.1mm)
Filtration capacity:	10.000 μ F
Output voltage ripple:	< 1mV
Trigger output:	2,5mm jack
Dimensions W x H x D:	206 x 71 x 209 mm (with sockets)
Weight:	3000g