

Polk Audio R200AE zvučnici za policu/stalak

Šifra: 17379

Kategorija proizvoda: Bookshelf Zvučnici

Proizvođač: Polk audio

Cena: **83.880,00** rsd

Collectible, limited-edition model, only 1,000 pairs produced
50th anniversary, serialized commemorative plaque with etched Matthew Polk signature
Same award-winning acoustics and performance as original R200
Upgraded aesthetics and components with authentic cherry wood veneer and more

A CELEBRATION OF FIFTY YEARS OF GREAT SOUND FOR ALL

We chose our most celebrated speaker in recent years, the Reserve R200, to commemorate Polk's 50th Anniversary with this special collector's edition model, limited to a one-time production run of 1,000 units worldwide. Signed by Matthew Polk and numbered on a unique, laser-etched backplate. Includes a certificate of authenticity.

LEGENDARY SOUND

COLLECTOR'S EDITION OF AN AWARD-WINNING ICON

Integrating acoustic innovations found in our flagship Legend Series, the original R200 earned The Absolute Sound's 2021 Bookshelf Loudspeaker of the Year and 2022 Editor's Choice accolades; the Reserve Series is Sound & Vision's Top Pick of 2022 and has earned countless 5-star reviews from Polk fans around the world.

A MODERN CLASSIC

SIGNATURE CHERRY WOOD FINISH AND REFINED COMPONENTS

This special-edition speaker embodies all the innovations that make the R200 a Polk classic, with distinctive touches worthy of a rare collectible—from its authentic oiled cherry wood veneer to upgraded crossovers and premium 24K gold-plated five-way binding posts.

INNACLE RING RADIATOR TWEETER

HIGH-RESOLUTION SOUND WHEREVER YOU SIT

The Pinnacle Ring Radiator Tweeter's unique waveguide provides broader high-frequency dispersion for a room-spanning sweet spot. With sound reproduction beyond 40kHz and ultra-fast and accurate transients, with the R200AE, you'll enjoy crisp clarity and detail wherever you're seated.

TURBINE CONE WOOFER

MULTIDIMENSIONAL MIDRANGE AND BASS

Relentless prototyping and refinement resulted in the striking Turbine Cone Woofer's unique ridged design. Its ultra-light, yet ultra-rigid cone provides sound reproduction with increased power, accuracy, and speed. You'll hear breathtaking midrange, detailed bass, and a wide dynamic range in everything you listen to.

PATENTED X-PORT

HEAR PURE, UNMASKED SOUND

Traditional ported speaker designs increase low- frequency performance, but often mask midrange details due to port resonances. Polk's proprietary X-Port uses specially tuned eigentone filters to cancel out unwanted resonances. With X-Port you get the best of both worlds: tight, distortion-free bass and a superbly detailed midrange.

ANTI-RESONANT CABINETS AND ANTI-DIFFRACTION GRILLES

ACOUSTICALLY OPTIMIZED INSIDE AND OUT

R200AE's acoustically transparent, magnetic grilles offer a clean look without interfering with sonic performance. Behind the grilles is a world of audio innovation. These rigid, acoustically inert cabinets have been carefully cross-braced and optimized through laser Doppler vibrometry to eliminate unwanted interior resonances.

PATENTED ACOUSTICS, CERTIFIED SONIC EXCELLENCE

The R200AE 50th Anniversary Edition features all the audio innovations that define the sound of our iconic bookshelf speaker, with upgraded components and refinements.

SIGNATURE SPEAKER TECHNOLOGIES

Designed and engineered in Baltimore, these special-edition speakers showcase award-winning acoustic innovations to deliver that iconic Polk sound you know and love.

REFINED INSIDE AND OUT

The R200AE 50th Anniversary Edition sounds—and looks—amazing, thanks to enhancements ranging from upgraded crossover components and binding posts to its stunning oiled cherry wood finish.

HI-RES AUDIO CERTIFIED

Uncover incredible clarity and detail in even the highest-resolution digital audio to experience music and movie sound in its purest form.

Specification

Tweeter	1" Pinnacle Ring Radiator
Mid-range/Mid-bass	-
Woofers	6 ½" Turbine Cone
Overall Frequency Response	39Hz - 50kHz
Frequency Response (-3dB limits)	51Hz - 38kHz
Recommended Amplifier Power	30 - 200W
Amplifier Output Compatibility	8Ω / 6Ω / 4Ω
Minimum Impedance (ohms)	3.8Ω
Sensitivity (2.83V/1m)	86dB