

Bowers & Wilkins 704 S3 Gloss Black - Podnostojeći zvučnik - DISPLAY MODEL

Šifra: 17450

Kategorija proizvoda: Podnostojeći Zvučnici

Proizvođač: Bowers & Wilkins



Cena: 197.880,00 rsd

Slim design, big sound

This elegant floor-standing loudspeaker is slimmer and easier to accommodate than ever. Perfect for superlative sound in smaller spaces.

A house for high frequencies

Carbon Dome tweeters are purpose-built for the 700 Series. Delivering a dramatic improvement on the aluminium double dome tweeter, they raise the breakup threshold to 47kHz, for pinpoint imaging accuracy and detail.

Truly amazing sound

Thanks to its composite construction, the Continuum™ cone avoids the abrupt transitions in behaviour that can impair the performance of a conventional drive unit. The result is a more open, neutral performance that delivers voices and instruments with precision and transparency.

Clean and clear

Every three-way loudspeaker in the new 700 Series has a dedicated midrange cone using four key Bowers & Wilkins technologies: the Continuum cone, FST™, Biomimetic Suspension and midrange decoupling, the latter ensuring minimal interference from the operation of the loudspeaker's bass drivers.

A triumph of science

Developed using advanced computer modelling techniques, the Aerofoil™ Profile bass cone has variable thickness, providing stiffness and rigidity where it's needed most. The result: deep and dynamic bass.

Size & weight

Dimensions	<p>Height: 925 mm cabinet only 964 mm including plinth Width: 165 mm cabinet only 252 mm including plinth Depth: 263 mm cabinet only 300 mm including grille and terminal 321 mm including plinth</p>
------------	---

Net weight	20.53kg
------------	---------

Technical details

Technical features	<p>Decoupled Carbon Dome tweeter Continuum™ cone FST™ midrange Decoupled midrange Aerofoil™ Profile bass cones Flowport™</p>
--------------------	--

Description	3-way vented-box system
-------------	-------------------------

Drive units	<p>1x ø25mm (1 in) Decoupled Carbon 1x ø130mm (5 in) Continuum cone FST 2x ø130mm (5 in) Aerofoil profile bass</p>
-------------	--

Frequency range	43Hz and 33kHz
-----------------	----------------

Frequency response	48Hz - 28kHz ±3dB
--------------------	-------------------

Sensitivity	88dB spl (2.83Vrms, 1m)
-------------	-------------------------

Harmonic distortion	<p>2nd and 3rd harmonics (90dB, 1m o <1% 100Hz - 22kHz <0.5% 300Hz - 20kHz</p>
---------------------	--

Nominal impedance	8Ω (minimum 3.1Ω)
Recommended amplifier power	30W - 150W into 8Ω on unclipped pr
Max recommended cable impedance	0.1Ω