

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## Bowers & Wilkins 704 S3 Gloss Black - Podnostojeći zvučnik - DISPLAY MODEL

Šifra: 17450  
Kategorija proizvoda: Podnostojeći Zvučnici  
Proizvođač: Bowers & Wilkins

**Cena: 197.880,00 rsd**

Bowers & Wilkins 704 S3 Gloss Black - Podnostojeći zvučnik - **Slim**

### design, big sound

This elegant floor-standing loudspeaker is slimmer and easier to accommodate than ever. Perfect for superlative sound in smaller spaces.

### A house for high frequencies

Carbon Dome tweeters are purpose-built for the 700 Series. Delivering a dramatic improvement on the aluminium double dome tweeter, they raise the breakup threshold to 47kHz, for pinpoint imaging accuracy and detail.

### Truly amazing sound

Thanks to its composite construction, the Continuum™ cone avoids the abrupt transitions in behaviour that can impair the performance of a conventional drive unit. The result is a more open, neutral performance that delivers voices and instruments with precision and transparency.

### Clean and clear

Every three-way loudspeaker in the new 700 Series has a dedicated midrange cone using four key Bowers & Wilkins technologies: the Continuum cone, FST™, Biomimetic Suspension and midrange decoupling, the latter ensuring minimal interference from the operation of the loudspeaker's bass drivers.

### A triumph of science

Developed using advanced computer modelling techniques, the Aerofoil™ Profile bass cone has variable thickness, providing stiffness and rigidity where it's needed most. The result: deep and dynamic bass.

### Size & weight

Dimensions	Height: 925 mm cabinet only 964 mm including plinth Width: 165 mm cabinet only 252 mm including plinth Depth: 263 mm cabinet only 300 mm including grille and terminals 321 mm including plinth
Net weight	20.53kg

## Technical details

Technical features	Decoupled Carbon Dome tweeter Continuum™ cone FST™ midrange Decoupled midrange Aerofoil™ Profile bass cones Flowport™
Description	3-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Carbon Dome tweeter 1x ø130mm (5 in) Continuum cone FST™ midrange 2x ø130mm (5 in) Aerofoil profile bass cones
Frequency range	43Hz and 33kHz
Frequency response	48Hz - 28kHz ±3dB
Sensitivity	88dB spl (2.83Vrms, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m on axis) <1% 100Hz - 22kHz <0.5% 300Hz - 20kHz
Nominal impedance	8Ω (minimum 3.1Ω)
Recommended amplifier power	30W - 150W into 8Ω on unclipped program
Max recommended cable impedance	0.1Ω