Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Bowers & Wilkins 704 S3 Gloss Black - Podnostojeći zvučnik - DISPLAY MODEL



Šifra: 17450
Kategorija prozivoda: Podnostojeći Zvučnici
Proizvođač: Bowers & Wilkins

Cena: 221.880,00 rsd

Slim design, big sound
This elegant floor-standing loudspeaker is slimmer and easier to accommodate than ever. Perfect for superlative sound in smaller spaces.

A house for high frequencies
Carbon Dome tweeters are purpose-built for the 700 Series. Delivering a dramatic improvement on the aluminium double dome tweeter, they raise the breakup threshold to 47kHz, for pinpoint imaging accuracy and detail.

Truly amazing sound
Thanks to its composite construction, the Continuum™ cone avoids the abrupt transitions in behaviour that can impair the performance of a conventional drive unit. The result is a more open, neutral performance that delivers voices and instruments with precision and transparency.

Clean and clear
Every three-way loudspeaker in the new 700 Series has a dedicated midrange cone using four key Bowers & Wilkins technologies: the Continuum cone, FST™, Biomimetic Suspension and midrange decoupling, the latter ensuring minimal interference from the operation of the loudspeaker’s bass drivers.

A triumph of science
Developed using advanced computer modelling techniques, the Aerofoil™ Profile bass cone has variable thickness, providing stiffness and rigidity where it’s needed most. The result: deep and dynamic bass.

Size & weight

Dimensions	Height: 925 mm cabinet only 964 mm including plinth Width: 165 mm cabinet only 252 mm including plinth Depth: 263 mm cabinet only 300 mm including grille and termina 321 mm including plinth
Net weight	20.53kg

Technical details

Technical features	Decoupled Carbon Dome tweeter Continuum™ cone FST™ midrange Decoupled midrange Aerofoil™ Profile bass cones Flowport™
Description	3-way vented-box system
Drive units	1x ø25mm (1 in) Decoupled Carbon 1x ø130mm (5 in) Continuum cone F 2x ø130mm (5 in) Aerofoil profile ba
Frequency range	43Hz and 33kHz
Frequency response	48Hz - 28kHz ±3dB
Sensitivity	88dB spl (2.83Vrms, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m o <1% 100Hz - 22kHz <0.5% 300Hz - 20kHz

Nominal impedance	8Ω (minimum 3.1Ω)
Recommended amplifier power	30W - 150W into 8Ω on unclipped pr
Max recommended cable impedance	0.1Ω

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.