**1090**e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

# Bowers & Wilkins 603 S3 Oak -Podnostojeći zvučnik

Šifra: 17840

Kategorija prozivoda: Podnostojeći Zvučnici

Proizvođač: Bowers & Wilkins

Cena: 119.880,00 rsd

Bowerst & Wilkins 603: S3: Oak - Podnostojeći zvučnik

### Layered, beautiful details

The new 603 S3 introduces our all-new Titanium Dome tweeter, which combines exceptional resolution and insight with smooth, refined high-frequency reproduction. The result? An accurate and immersive insight into your favourite music.

#### Truly amazing sound

603 S3 introduces our new and even more acoustically transparent tweeter grille mesh, first

27.5kg (60.6 l

developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

#### **Precision and transparency**

Thanks to its composite construction, the Continuum cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. With 603 S3, experience a more open, neutral performance that delivers voices and instruments with precision and transparency.

## **Upgraded speaker terminals**

Derived from the speaker terminals recently introduced in our 700 Series range, the speaker terminals on the new 603 S3 feature an improved layout and a cleaner signal path between your amplifier and your loudspeakers.

## 600 Series

The essential loudspeakers for music lovers.

#### Size & weight

Net weight

		Height: 985 m
		1,020 mm (40
		Width: 190 m
[	Dimensions	260 mm (10.2
		Depth: 340 m
		368 mm (14.5
		402 mm (15.8
I		

## **Technical details**

Technical features	Decoupled Do Continuum™ ( Paper bass co Flowport™
Description	3-way vented-
Drive units	1x ø25mm (1 1x ø150mm (6 2x ø165mm (6
Frequency range	-6dB 29Hz - 3:
Frequency response (+/-3dB from reference axis)	46Hz - 28kHz
Sensitivity (on axis at 2.83Vrms at 1m)	90dB
Harmonic distortion	2nd and 3rd h <1% 100Hz - <0.5% 350Hz
Nominal impedance	8Ω (minimum
Recommended amplifier power	30W - 200W ii
Max recommended cable impedance	0.1Ω

## Finishes

Cabinet finishes	Black White Oak
Grille finishes	Grey (White