

logo not found or type unknown

Firma: Player Plus doo  
Adresa: Svetogorska 9  
Telefon: +381 11 3347 442  
Fax: +381 11 3347 615  
PIB: 106966344  
E-mail: porudzbine@player.rs

## Bowers & Wilkins 603 S3 White - Podnostojeći zvučnik

Šifra: 17841  
Kategorija proizvoda: Podnostojeći Zvučnici  
Proizvođač: Bowers & Wilkins

Cena: 95.880,00 rsd

developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

### Precision and transparency

Thanks to its composite construction, the Continuum cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. With 603 S3, experience a more open, neutral performance that delivers voices and instruments with precision and transparency.

### Upgraded speaker terminals

Derived from the speaker terminals recently introduced in our 700 Series range, the speaker terminals on the new 603 S3 feature an improved layout and a cleaner signal path between your amplifier and your loudspeakers.

### 600 Series

The essential loudspeakers for music lovers.

### Size & weight

Dimensions

Height: 985 mm  
1,020 mm (40.3 in)  
Width: 190 mm  
260 mm (10.2 in)  
Depth: 340 mm  
368 mm (14.5 in)  
402 mm (15.8 in)

Net weight

27.5kg (60.6 lb)

## Bowers & Wilkins 603 S3 White - Podnostojeći zvučnik

### Layered, beautiful details

The new 603 S3 introduces our all-new Titanium Dome tweeter, which combines exceptional resolution and insight with smooth, refined high-frequency reproduction. The result? An accurate and immersive insight into your favourite music.

### Truly amazing sound

603 S3 introduces our new and even more acoustically transparent tweeter grille mesh, first developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

Technical details

Technical features	Decoupled Driver Continuum™ Paper bass cone Flowport™
Description	3-way vented
Drive units	1x ø25mm (1 1x ø150mm (6 2x ø165mm (6
Frequency range	-6dB 29Hz - 30
Frequency response (+/-3dB from reference axis)	46Hz - 28kHz
Sensitivity (on axis at 2.83Vrms at 1m)	90dB
Harmonic distortion	2nd and 3rd h <1% 100Hz - <0.5% 350Hz
Nominal impedance	8Ω (minimum
Recommended amplifier power	30W - 200W in
Max recommended cable impedance	0.1Ω

Finishes

Cabinet finishes	Black White Oak
Grille finishes	Grey (White a