

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Bowers & Wilkins 606 S3 White - Zvučnik za stalak/policu

Šifra: 17844

Kategorija proizvoda: Bookshelf Zvučnici

Proizvođač: Bowers & Wilkins

Cena: 53.880,00 rsd

Bowers & Wilkins 606 S3 White - Zvučnik za stalak/policu

An
icon

enhanced

The new 606 S3 takes the award-winning 606 formula and evolves it. By complementing the Continuum cone and Titanium Dome tweeter with upgraded speaker terminals, and a subtly modernised design, 606 is now even more appealing to even more music lovers.

Layered, beautiful details

The new 606 S3 introduces our all-new Titanium

Dome tweeter, which combines exceptional resolution and insight with smooth, refined high-frequency reproduction. The result? An accurate and immersive insight into your favourite music.

Truly amazing sound

606 S3 introduces our new and even more acoustically transparent tweeter grille mesh, first developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

Precision and transparency

Thanks to its composite construction, the Continuum cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. With 606 S3, experience a more open, neutral performance that delivers voices and instruments with precision and transparency.

Upgraded speaker terminals

Derived from the speaker terminals recently introduced in our 700 Series range, the speaker terminals on the new 606 S3 feature an improved layout and a cleaner signal path between your amplifier and your loudspeakers.

600 Series

The essential loudspeakers for music lovers.

Size & weight

Dimensions

Height: 344 mm
Width: 189 mm
Depth: 300 mm
328 mm (12.9

Net weight

7.05kg (15.5 lb)

Technical details

Technical features

Decoupled Driver
Continuum™
Flowport™

Frequency response (+/-3dB from reference axis)

52Hz - 28kHz

Description

2-way vented

Drive units

1x ø25mm (1")
1x ø165mm (6.5")

Frequency range

-6dB 40Hz - 30kHz

Sensitivity (on axis at 2.83Vrms at 1m)

88dB

Harmonic distortion

2nd and 3rd h
<1% 100Hz -
<0.5% 150Hz

Nominal impedance

8Ω (minimum)

Recommended amplifier power

30W - 120W in

Max recommended cable impedance

0.1Ω

Finishes

Cabinet finishes	Black
Grille finishes	Grey (White a