

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Bowers & Wilkins HTM6 S3 Black - Centralni zvučnik

Šifra: 17848
Kategorija proizvoda: Centralni Zvučnici
Proizvođač: Bowers & Wilkins

Cena: 77.880,00 rsd

Bowers & Wilkins HTM6 S3 Black - Centralni zvučnik

Celebrate clarity
Powerful enough to partner with 603 S3 and compact enough to fit with any piece of furniture, HTM6 S3 brings more realism and accuracy to your home theater experience.

Layered, beautiful details
The new HTM6 S3 introduces our all-new Titanium Dome tweeter, which combines exceptional resolution and insight with smooth, refined high-frequency reproduction. The result? An accurate and immersive insight into your favourite music.

Truly amazing sound
HTM6 S3 introduces our new and even more acoustically transparent tweeter grille mesh, first developed for our revered Signature models. Alongside the new Titanium Dome tweeter, the resolution and realism is exceptional.

Precision and transparency
Thanks to its composite construction, the Continuum cone avoids the abrupt transitions in behavior that can impair the performance of a conventional drive unit. With HTM6 S3, experience a more open, neutral performance that delivers voices and instruments with precision and transparency.

Upgraded speaker terminals
Derived from the speaker terminals recently introduced in our 700 Series range, the speaker terminals on the new HTM6 S3 feature an improved layout and a cleaner signal path between your amplifier and your loudspeakers.

600 Series
The essential loudspeakers for music lovers.

Size & weight

Dimensions	Height: 160 mm Width: 480 mm Depth: 255 mm 283 mm (11.2 in)
Net weight	7.7kg (17lb)

Technical details

Technical features	Decoupled Drive Continuum™ and Flowport™
Description	2-way vented design
Drive units	1x ø25mm (1" tweeter) 2x ø130mm (5" woofer)
Frequency range	-6dB 42Hz - 30kHz
Frequency response	72Hz - 28kHz
Sensitivity	87dB spl (on axis, 1m)
Harmonic distortion	2nd and 3rd harmonics <1% 100Hz - 1kHz <0.5% 120Hz - 1kHz
Nominal impedance	8Ω (minimum)
Recommended amplifier power	30W - 120W in
Max recommended cable impedance	0.1Ω

Finishes

Cabinet finishes	Black
Grille finishes	Black (Black)