

Biamp Parlé TCM-1EX Black - Konferencijski mikrofon

Šifra: 17961
Kategorija proizvoda: Konferencijski / Instalacijski
Mikrofoni
Proizvođač: Biamp



Cena: 71.880,00 rsd

GENERAL	
Height	Microphone: 2 inches (51 mm) Plenum Box: 2 inches (51 mm)
Width	Microphone: 2.5 inches (63 mm) Plenum Box: 4 inches (102 mm)
Depth	Microphone: 2.5 inches (63 mm) Plenum Box: 5.25 inches (133 mm)
Weight	Microphone: 0.4 lbs (0.2 kg) Plenum Box: 0.8 lbs (0.4 kg)
Accessories	Plenum Box (included): Connectors: Two RJ-45: one between TCM-1EX plenum box and TCM-1 or TCM-1A, the other between TCM-1EX plenum box and additional TCM-1EX plenum box; 2-pin 3.5 mm Phoenix connector to TCM-1EX microphone Digital Interface: Custom/Proprietary Max Distance Between Devices: 33 feet (10 meters) between TCM plenum boxes
POWER	
Power	Plenum Box: Custom/Proprietary
Power Indicator(s)	Plenum Box: Link Indicator (Green LED) Microphone: Mute Indicator (Green/Red LED)

AUDIO	
Microphone	Pendant: Microphone Technology: 8-Element Digital Array Polar Pattern: Beamformed Sensitivity (94dB SPL, 1kHz): > 70dB Digital Interface: Custom/Proprietary Connector: Custom 2-pin (cable length 10 feet [3 meters])
Frequency Response	(150 Hz - 16 kHz): \pm 3dB
Dynamic Range	(THD+N < 10%): 92dB, A-Weighted
SPL	(at 0.5% THD): 106dB
CERTIFIED SOLUTIONS	
TAA Compliant	TAA Compliant
COMPLIANCE	
Certifications	FCC Part 15B (USA) CE marked (Europe) UL and C-UL listed (USA and Canada) RoHS Directive (Europe) Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces

Key Features

- Must be used with a Parl  TCM-1 or TCM-1A microphone
- Beamtracking technology actively tracks and intelligently mixes conversations
- Three 120-degree zones for 360-degree coverage
- Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces
- Pendant microphone available in either white or black
- Optional tile bridge mounting accessory available
- Additional RJ-45 for daisy-chain connection to a TCM-1EX microphone (maximum of three microphones per daisy chain)
- CE marked, UL listed, and RoHS compliant
- Compliant with the US Trade Agreement Act (TAA)