

ARCAM Radia A15 Integrisano Pojačalo

Šifra: 17966
Kategorija proizvoda: Integrisana Pojačala
Proizvođač: ARCAM

Cena: 119.880,00 rsd

from your phone or tablet, no matter what you are playing. It can also connect to Bluetooth headphones so your listening experience can continue sensitively after dark.

Hi-res audio is included with high resolution digital audio inputs included.

Like any ARCAM integrated amplifier, we pay particular attention to the built in phono stage to ensure your records sound as lush and engaging as possible.

- ARCAM Class AB amplification - provides brilliant musicality
- 80W per channel 8Ω - powers loudspeakers with dynamics.
- Bluetooth with aptX™ Adaptive Technology - for the best sound with the most convenience
- Specially selected components and materials - to deliver on sound quality
- Wired or Wireless Headphones - connect your headphones for quiet listening with, or without wires
- All new Radia design - Purposeful yet playful
- MM phono stage - ready for Turntables
- Hi-Res Digital Audio Inputs
- Plastic Free Packaging - for easy disposal of natural materials

ARCAM Radia A15 Integrisano Pojačalo The "A" in

ARCAM stands for Amplification - this is our core competence. The A15 is the latest in more than 45 years of amplifier design and manufacture. New components and materials have been painstakingly analysed and reviewed to ensure brilliant sound performance.

So you can play music straight out of the box, the ARCAM A15 includes a Bluetooth solution with Qualcomm AptX Adaptive technology. This provides up to 24-bit HD audio for the best sound quality

Specification	
Continuous power output (0.5% THD), per channel	80W (8Ω), 120W (4Ω)
Harmonic distortion, 80% power, 8Ω at 1kHz	0.002%
Number of analog inputs	3 (RCA pairs)
Signal-to-noise ratio (A-wtd, ref. 50W, 1V input)	106dB

Frequency response	20Hz—20kHz ± 0.2dB
Phono (MM) Input impedance	47kΩ + 100pF
Phono (MM) Input frequency response (ref. RIAA curve)	20Hz—20kHz ± 1dB
Phono (MM) Input signal-to-noise ratio (A-wtd, ref. 50W, 0dBFS)	109dB
Coaxial (RCA) supported sample rates (kHz)	192, 176.4, 96, 88.2, 48, 44.1
Optical (Toslink) supported sample rates (kHz)	192, 176.4, 96, 88.2, 48, 44.1
Supported bit depths (bit)	24, 16
Frequency response (filter 1)	20Hz—20kHz ± 0.2dB
Headphone output maximum output level (RMS) into 32Ω/300Ω	2.5V/5Vrms
Headphone load range	16Ω - 2kΩ
Mains voltage	100V or 110–120V or 220–240V, 50–60Hz
Power consumption (maximum)	500W
Power consumption (standby)	<0.5W
Dimensions W x D (including speaker terminals) x H (including feet)	431 x 344 x 98mm
Weight (net)	10kg
Weight (packed)	13kg
Supplied accessories	Mains lead(s), Remote control with 2 x AAA batteries, Quick Start Guide, Important Safety Instructions