

TASCAM CD-400UDAB



Šifra: 17980

Kategorija proizvoda: CD Plejeri

Proizvođač: TASCAM

Cena: 71.880,00 rsd

General

Supported media	
USB memory	512 MB – 64 GB
SD card	512 MB – 2 GB
SDHC card	4–32 GB
CD	CD-DA, CD-ROM, CD-R, CD-RW (CD-DA format only)
Supported file systems	FAT16, FAT32
Supported file formats	
CD-DA	44.1 kHz, 16 bit
MP3	44.1 / 48 kHz, 32–320 kbit/s and VBR (MPEG1/2 Audio Layer 3)
WAV (USB/SD only)	44.1/48 kHz, 16 bit
WMA	44.1/48 kHz, 32–320 kbit/s and VBR (WMA v9 standard, DRM not supported)
AAC (USB/SD only)	44.1/48 kHz, 8–320 kbit/s and VBR (MPEG4 AAC-LC audio stream)
Number of audio channels	2 channels (stereo), 1 channel (mono)

General

Recording file format	MP3 (44.1 kHz, 96/128/192/320 kbit/s)
-----------------------	---------------------------------------

Bluetooth receiver

Bluetooth version	v4.2
-------------------	------

Output class	Class 2
--------------	---------

Supported profiles	A2DP, AVRCP
--------------------	-------------

Supported A2DP codecs	SBC, AAC, aptX
-----------------------	----------------

Supported A2DP content protection	SCMS-T
-----------------------------------	--------

Tuner

Frequency range	FM: 87.5–108 MHz DAB: Band III, 174–240 MHz
-----------------	--

Antenna connector	F-type (female), 50 Ω, unbalanced
-------------------	-----------------------------------

Analogue audio inputs and outputs

AUX analogue audio input (unbalanced)	3.5-mm TRS mini-jack
---------------------------------------	----------------------

Nominal input level	−20 dBV (0.1 Vrms)
---------------------	--------------------

Maximum input level	−4 dBV (0.63 Vrms)
---------------------	--------------------

Analogue audio inputs and outputs

Input impedance	$\geq 10\text{ k}\Omega$
Main analogue audio outputs (balanced)	XLR-3-32 (1: GND, 2: HOT, 3: COLD)
Nominal output level	+4 dBu (1.23 Vrms, Output Attenuation: 0 dB)
Maximum output level	+20 dBu (7.75 Vrms, Output Attenuation: 0 dB)
Output impedance	100 Ω
Main analogue audio outputs (unbalanced)	RCA
Nominal output level	-10 dBV (0.316 Vrms, Output Attenuation: 0 dB)
Maximum output level	+6 dBV (2.0 Vrms, Output Attenuation: 0 dB)
Output impedance	200 Ω
Tuner analogue audio outputs (unbalanced)	RCA
Nominal output level	-10 dBV (0.316 Vrms, Output Attenuation: 0 dB)
Maximum output level	+6 dBV (2.0 Vrms, Output Attenuation: 0 dB)
Output impedance	200 Ω
Headphones output	6.3 mm stereo jack
Maximum output power	$\geq 20\text{ mW} + 20\text{ mW}$ (THD+N $\leq 0.1\%$, 32 Ω load)

Control I/O

RS-232C	D-sub 9 pin
---------	-------------

Audio performance

Audio performance

Frequency response	20 Hz – 20 kHz, ± 1 dB (Fs: 44.1 kHz, 48 kHz, JEITA)
--------------------	--

Total harmonic distortion	≤ 0.005 % (JEITA)
---------------------------	------------------------

S/N ratio	≥ 95 dB (JEITA)
-----------	----------------------

Dynamic range	≥ 90 dB (JEITA)
---------------	----------------------

Channel crosstalk	≥ 90 dB (JEITA)
-------------------	----------------------

Power supply and other specifications

Mains power	AC 100–240 V, 50/60 Hz
-------------	------------------------

Power consumption	20 W
-------------------	------

Overall dimensions (W × H × D)	483 mm × 47 mm × 296 mm
--------------------------------	-------------------------

Weight	3.3 kg
--------	--------

Operating temperature range	5–35 °C
-----------------------------	---------

Included accessories	Removable mains power cord, wireless remote control (RC-CD400), rack-mounting screw kit, FM antenna, owner's manual/warranty
----------------------	--

Optional accessory	IF-E100 Ethernet option card, allows the unit to be controlled over a network (Telnet protocol)
--------------------	---