

TASCAM PORTACAPTURE X6

TASCAM PORTACAPTURE X6

Recording media	microSD cards (64MB - 2GB), microSDHC cards (4GB - 32GB), microSDXC cards (48GB - 512GB) *Class 10 or higher required
Šifra: 17982 Kategorija proizvoda: Snimači/Rekorderi Proizvođač: TASCAM	
Cena: 39.480,00 rsd	

Recording / playback formats	
WAV (BWF)	44.1k/48k/96kHz, 16/24-bit, 32-bit float
MP3	44.1k/48kHz, 128k/192k/256k/320kbps
Number of channels	
Input channels	4 channels maximum
Recording tracks	6 tracks maximum (4 tracks, stereo mix)
Analog audio input ratings	
Mic inputs (balanced)	
Input jacks 3-4(when INPUT SELECT set to MIC)	
Connectors	XLR-3-31 equivalent (1: GND, 2: HOT, 3: COLD) Note: supports phantom power only when MIC input selected
Input impedance	2.2kΩ or higher
Maximum input level	+2dBV
Minimum input level	-75dBV

Input jacks 3-4 (when INPUT SELECT set to LINE)	
--	--

Connectors	XLR-3-31 equivalent (1: GND, 2: HOT, 3: COLD)
Input impedance	9k Ω or higher
Nominal input level	+4dBu(GAIN setting at minimum)
Maximum input level	+24dBu
Minimum input level	-53dBu
Line input (unbalanced)	MIC/EXT IN jack (can provide plugin power)
Connectors	3.5mm (1/8") stereo mini jack
Input impedance	10 k Ω or higher (when plug-in power is off) 1.8 k Ω or higher (when plug-in power is on)
Nominal input level	-20 dBV(GAIN setting at minimum)
Maximum input level	0 dBV
Minimum input level	-67 dBV
Analog audio output ratings	
Line output (unbalanced)	LINE OUT jack
Connectors	3.5mm (1/8") stereo mini jack
Output impedance	210 Ω
Nominal output level	-14dBV
Maximum output level	+6 dBV
Headphone output	headphone jack
Connectors	3.5mm (1/8") stereo mini jack
Maximum output	45mW + 45mW (THD+N 0.1% or less, into 32 Ω load)
Working impedance	16ohms to 400ohms
Built-in speaker	0.4 W (mono)
USB	

Port	USB Type-C
Transfer mode	USB 2.0 Hi-Speed
Device classes	mass storage,USB audio 2.0 (USB class compliant)
USB audio	
Sampling frequencies	44.1, 48, 96 kHz
Quantization bit depth	24-bit
Number of input channels	6 (output from unit)
Number of output channels	2 (input to unit)
Bluetooth device connector	For Bluetooth adapter (AK-BT1) only
Portacapture Control	
iOS/iPadOS devices	iOS 16/iPadOS 16,iOS 15/iPadOS 15,iOS 14/iPadOS 14
Android devices	Android 11,Android 10 Note: Compatibility has been confirmed, but this does not guarantee operation with all devices.
Power	4 AA batteries (Alkaline, Ni-MH or Lithium-ion) USB bus power from a computer TASCAM PS-P520U AC adapter (sold separately)
Power consumption	7.5W (maximum)
Dimensions	75 × 174.3 × 37.2 mm (W× H× D, excluding protrusions)
Weight	365/265g (with/without batteries)
Operating temperature range	0 - 40°C
Included	Portacapture X6 × 1 AA alkaline batteries × 4 Owner's Manual (including warranty) × 1 TASCAM ID registration guide × 1