Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Arturia Audiofuse Studio

Šifra: 18066
Kategorija prozivoda: USB Zvučne kartice
Proizvođač: Arturia



Cena: 86.280,00 rsd

Channels of I/O	18 Input / 20 Output at 192 kHz
Maximum Sampling Rate	192 kHz / 24-Bit
Number of Microphone Inputs	4 Preamps
Analog Audio I/O	**4 x** Combo XLR-1/4" TRS Input **1 x** Stereo RCA Coaxial Line Input **4 x** 1/4" TRS Input **4 x** 1/4" TRS Insert In/Out **4 x** 1/4" TRS Monitor Output **2 x** 1/4" TRS Headphone Output **2 x** 1/8" / 3.5 mm TRS Headphone Output

Digital Audio I/O	**2 x** TOSLINK Optical ADAT Input **2 x** TOSLINK Optical ADAT Output **1 x** RCA Coaxial S/PDIF Input (Word Clock Support) **1 x** RCA Coaxial S/PDIF Output (Word Clock Support)

Host Connection	USB-C

Power Requirements	AC/DC Power Adapter (Included)

Maximum Sampling Rate	192 kHz / 24-Bit

Number of Microphone Inputs	4 Preamps

Signal Processing

Gain/Trim Range	**Line/Hi-Z Inputs:** -15 dB to +36 dB **Mic Inputs:** 3 dB to 76 dB

Connectivity

Analog Audio I/O	**4 x** Combo XLR-1/4" TRS Input **1 x** Stereo RCA Coaxial Line Input **4 x** 1/4" TRS Input **4 x** 1/4" TRS Insert In/Out **4 x** 1/4" TRS Monitor Output **2 x** 1/4" TRS Headphone Output **2 x** 1/8" / 3.5 mm TRS Headphone Output
Phantom Power	48 V (Selectable on Individual Inputs)
Digital Audio I/O	**2 x** TOSLINK Optical ADAT Input **2 x** TOSLINK Optical ADAT Output **1 x** RCA Coaxial S/PDIF Input (Word Clock Support) **1 x** RCA Coaxial S/PDIF Output (Word Clock Support)
Host Connection	USB-C
Host Connection Protocol	USB 2.0
Sync I/O	**1 x** RCA Coaxial Word Clock Input (Shared with S/PDIF) **1 x** RCA Coaxial Word Clock Output (Shared with S/PDIF)
MIDI I/O	**1 x** DIN 5-Pin Input (on Included Breakout Cable) **1 x** DIN 5-Pin Output (on Included Breakout Cable)
Wireless	Bluetooth
Wireless Connectivity	Bluetooth

Performance

Frequency Response	**Mic, Line, Hi-Z Inputs:** 20 Hz to 20 kHz ±0.8 dB
Maximum Input Level	**Line Inputs:** +24 dBu **Mic Inputs:** +11 dBu **Hi-Z Inputs:** +18 dBu **Insert Inputs:** +18 dBu
Maximum Output Level	**Insert Outputs:** +18 dBu **Outputs:** +24 dBu **Headphone Outputs:** +10 dBu
Impedance	**Line Inputs:** 20 Kilohm (Balanced) 10 Kilohm (Unbalanced) **Mic Inputs:** 3.4 Kilohm (Mic Level) **Hi-Z Inputs:** 1.1 Megohm **Aux Inputs:** 20 Kilohms (Balanced) 10 Kilohms (Unbalanced) **Line Outputs:** 120 Ohms (Balanced) **Headphone Outputs:** 33 Ohm
Dynamic Range	**Line Inputs:** 117 dBA **Hi-Z Inputs:** 117 dBA **Headphone Outputs:** 102 dBA

THD+N	**Line Inputs:** 106 dBA **Mic Inputs:** 104 dBA **Hi-Z Inputs:** 104 dBA **Outputs:** 104 dBA **Headphone Outputs:** 87 dBA
EIN	**Mic Inputs:** 129.5 dBu

Digital Audio

Sample Rates	Up to 192 kHz (AD/DA Conversion)
Bit Depths	Up to 24-Bit (AD/DA Conversion)
Sync Sources	ADAT, S/PDIF

Compatibility

Processor Requirement	**Mac:** Intel **PC:** Intel
RAM Requirements	4 GB

Storage Requirements	1 GB

Power

Power Requirements	AC/DC Power Adapter (Included)

Dimensions	10.4 x 6.3 x 2.8" / 264.2 x 160 x 71.1 mm

Packaging Info

Package Weight	6.555 lb

Box Dimensions (LxWxH)	12.7 x 8.3 x 6.4"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.