

Arturia Audiofuse Studio

Šifra: 18066
Kategorija proizvoda: USB Zvučne kartice
Proizvođač: Arturia



Cena: 77.880,00 rsd

Channels of I/O	18 Input / 20 Output at 192 kHz
Maximum Sampling Rate	192 kHz / 24-Bit
Number of Microphone Inputs	4 Preamps
Analog Audio I/O	<ul style="list-style-type: none">4 x Combo XLR-1/4" TRS Input1 x Stereo RCA Coaxial Line Input4 x 1/4" TRS Input4 x 1/4" TRS Insert In/Out4 x 1/4" TRS Monitor Output2 x 1/4" TRS Headphone Output2 x 1/8" / 3.5 mm TRS Headphone Output

Digital Audio I/O

- 2 x TOSLINK Optical ADAT Input
- 2 x TOSLINK Optical ADAT Output
- 1 x RCA Coaxial S/PDIF Input (Word Clock Support)
- 1 x RCA Coaxial S/PDIF Output (Word Clock Support)

Host Connection

USB-C

Power Requirements

AC/DC Power Adapter (Included)

Maximum Sampling Rate

192 kHz / 24-Bit

Number of Microphone Inputs

4 Preamps

Signal Processing

Gain/Trim Range

Line/Hi-Z Inputs:
-15 dB to +36 dB
Mic Inputs:
3 dB to 76 dB

Connectivity

Analog Audio I/O	4 x Combo XLR-1/4" TRS Input 1 x Stereo RCA Coaxial Line Input 4 x 1/4" TRS Input 4 x 1/4" TRS Insert In/Out 4 x 1/4" TRS Monitor Output 2 x 1/4" TRS Headphone Output 2 x 1/8" / 3.5 mm TRS Headphone Output
Phantom Power	48 V (Selectable on Individual Inputs)
Digital Audio I/O	2 x TOSLINK Optical ADAT Input 2 x TOSLINK Optical ADAT Output 1 x RCA Coaxial S/PDIF Input (Word Clock Support) 1 x RCA Coaxial S/PDIF Output (Word Clock Support)
Host Connection	USB-C
Host Connection Protocol	USB 2.0
Sync I/O	1 x RCA Coaxial Word Clock Input (Shared with S/PDIF) 1 x RCA Coaxial Word Clock Output (Shared with S/PDIF)
MIDI I/O	1 x DIN 5-Pin Input (on Included Breakout Cable) 1 x DIN 5-Pin Output (on Included Breakout Cable)
Wireless	Bluetooth
Wireless Connectivity	Bluetooth

Performance

Frequency Response

Mic, Line, Hi-Z Inputs:
20 Hz to 20 kHz ± 0.8 dB

Maximum Input Level

Line Inputs:
+24 dBu
Mic Inputs:
+11 dBu
Hi-Z Inputs:
+18 dBu
Insert Inputs:
+18 dBu

Maximum Output Level

Insert Outputs:
+18 dBu
Outputs:
+24 dBu
Headphone Outputs:
+10 dBu

Impedance

Line Inputs:
20 Kilohm (Balanced)
10 Kilohm (Unbalanced)
Mic Inputs:
3.4 Kilohm (Mic Level)
Hi-Z Inputs:
1.1 Megohm
Aux Inputs:
20 Kilohms (Balanced)
10 Kilohms (Unbalanced)
Line Outputs:
120 Ohms (Balanced)
Headphone Outputs:
33 Ohm

Dynamic Range

Line Inputs:
117 dBA
Hi-Z Inputs:
117 dBA
Headphone Outputs:
102 dBA

THD+N	Line Inputs: 106 dBA Mic Inputs: 104 dBA Hi-Z Inputs: 104 dBA Outputs: 104 dBA Headphone Outputs: 87 dBA
EIN	Mic Inputs: 129.5 dBu

Digital Audio

Sample Rates	Up to 192 kHz (AD/DA Conversion)
Bit Depths	Up to 24-Bit (AD/DA Conversion)
Sync Sources	ADAT, S/PDIF

Compatibility

Processor Requirement	Mac: Intel PC: Intel
RAM Requirements	4 GB

Storage Requirements	1 GB
----------------------	------

Power

Power Requirements	AC/DC Power Adapter (Included)
Dimensions	10.4 x 6.3 x 2.8" / 264.2 x 160 x 71.1 mm

Packaging Info

Package Weight	6.555 lb
Box Dimensions (LxWxH)	12.7 x 8.3 x 6.4"