Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Arturia AudioFuse 16Rig USB-C Audio/MIDI Interface



Šifra: 18075
Kategorija prozivoda: USB Zvučne kartice
Proizvođač: Arturia

Cena: 110.027,00 rsd

Channels of I/O	32 Inputs / 28 Outputs
Maximum Sampling Rate	192 kHz / 24-Bit
Number of Microphone Inputs	2
Analog Audio I/O	**16 x** 1/4" TRS Balanced Line Input **2 x** Combo XLR-1/4" TRS Balanced Mic/Line/Hi-Z Input (Front Panel) **1 x** 1/8" / 3.5 mm TRS Line Input (Front Panel) **10 x** 1/4" TRS Balanced Line Output **2 x** 1/4" TRS Balanced/Unbalanced Line/Headphone/Re-Amp Output (Shared with Rear Panel Input) **1 x** 1/4" TRS Headphone Output **1 x** 1/8" / 3.5 mm TRS Headphone Output

Digital Audio I/O	**2 x** TOSLINK Optical ADAT Input **2 x** TOSLINK Optical ADAT Output

Host Connection	**1 x** USB-C (Class-Compliant)

OS Compatibility	macOS 10.13 or Later Windows 10 or Later **As of October, 2023: Check with manufacturer for the most up-to-date compatibility*

Power Requirements	AC/DC Power Adapter (Included)

Channels of I/O	32 Inputs / 28 Outputs

Built-In DSP	Yes

Maximum Sampling Rate	192 kHz / 24-Bit

Number of Microphone Inputs	2

Built-In Microphone	No

Input Level Adjustment	Knob

Expansion Slots	No

Signal Processing

Pad	**Mic:** -20 dB (Switchable per Channel) **Line:** -12 dB (Switchable per Channel) **Line:** -10 dB (Switchable per Channel) **Hi-Z:** -10 dB (Switchable per Channel)

Solo/Mute	Solo, Mute per Master

Connectivity

Analog Audio I/O	**16 x** 1/4" TRS Balanced Line Input **2 x** Combo XLR-1/4" TRS Balanced Mic/Line/Hi-Z Input (Front Panel) **1 x** 1/8" / 3.5 mm TRS Line Input (Front Panel) **10 x** 1/4" TRS Balanced Line Output **2 x** 1/4" TRS Balanced/Unbalanced Line/Headphone/Re-Amp Output (Shared with Rear Panel Input) **1 x** 1/4" TRS Headphone Output **1 x** 1/8" / 3.5 mm TRS Headphone Output

Phantom Power	48 V, Selectable On/Off

Digital Audio I/O	**2 x** TOSLINK Optical ADAT Input **2 x** TOSLINK Optical ADAT Output

Host Connection	**1 x** USB-C (Class-Compliant)

Host Connection Protocol	USB 2.0
USB (Non-Host)	**3 x** USB-A (External Storage, MIDI I/O)
Sync I/O	**1 x** BNC Word Clock Input **1 x** BNC Word Clock Output **1 x** 1/8" / 3.5 mm Clock Output
Network I/O	No
MIDI I/O	**1 x** DIN 5-Pin Input **2 x** DIN 5-Pin Output/Thru
Wireless	No

Performance

Frequency Response	**Line Inputs:** 20 Hz to 20 kHz ±0.06 dB **Hi-Z Inputs:** 20 Hz to 20 kHz ±0.1 dB **Mic Inputs:** 20 Hz to 20 kHz ±0.08 dB **Monitor Outputs:** 20 Hz to 20 kHz ±0.02 dB **Line Outputs:** 20 Hz to 20 kHz ±0.04 dB
Maximum Input Level	**Line:** +24 dBu (Rear) +22 dBu (Front) **Hi-Z:** 20 dBu **Mic:** 22 dBu

Maximum Output Level	**Monitor:** 20 dBu **Line:** 24 dBu **Headphone:** 14.4 dBu
Headphone Output Power	271 mW into 33 Ohms
Impedance	**Line Inputs:** 20 Kilohm **Hi-Z Inputs:** 1.1 Megohm **Mic Inputs:** 2.7 Kilohms **Monitor Outputs:** 240 Ohms (Balanced) 120 Ohms (Unbalanced) **Line Outputs:** 240 Ohms (Balanced) 120 Ohms (Unbalanced) **Headphone Outputs:** 5 Ohms
Dynamic Range	**Line Inputs:** 118 dBA **Hi-Z Inputs:** 114 dBA **Mic Inputs:** 117 dBA **Monitor Outputs:** 126 dBA **Line Outputs:** 120 dBA **Headphone Outputs:** 109 dBA

THD+N	**Line Inputs:** -113 dBA **Hi-Z Inputs:** -105 dBA **Mic Inputs:** -110 dBA **Speaker Outputs:** -114 dBA **Line Outputs:** -106 dBA **Headphone Outputs:** -103 dBA
EIN	-129.5 dBu A-Weighted

Digital Audio

Sample Rates	44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz
Bit Depths	24-Bit
Sync Sources	ADAT, Internal, Word Clock

Audio Storage & Playback

Media/Memory Card Slot	No

Compatibility

OS Compatibility	macOS 10.13 or Later Windows 10 or Later **As of October, 2023: Check with manufacturer for the most up-to-date compatibility*
Included Software	No
Processor Requirement	**Mac:** Intel Core i5 Apple M1
RAM Requirements	4 GB
Storage Requirements	4 GB
Mobile App Compatible	No **As of October, 2023: Check with manufacturer for the most up-to-date compatibility*

Power

Power Requirements	AC/DC Power Adapter (Included)
AC/DC Power Adapter	Included

Physical

Rackmount Size	1 RU (with Included Hardware)

Dimensions	17.3 x 11.6 x 1.7" / 43.9 x 29.5 x 4.3 cm

Packaging Info

Package Weight	11.37 lb

Box Dimensions (LxWxH)	23.9 x 13.4 x 5.4"

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.