

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Arturia AudioFuse 16Rig USB-C Audio/MIDI Interface

Arturia AudioFuse 16Rig USB-C Audio/MIDI Interface

32 Inputs / 28 Outputs

Šifra: 18075

Kategorija proizvoda: USB Zvučne kartice

Proizvođač: Arturia
Maximum Sampling Rate

192 kHz / 24-Bit

Cena: 124.680,00 rsd

Number of Microphone

2

Inputs

Analog Audio I/O

16 x 1/4" TRS Balanced Line Input
2 x Combo XLR-1/4" TRS Balanced Mic/Line/Hi-Z Input (Front Panel)
1 x 1/8" / 3.5 mm TRS Line Input (Front Panel)
10 x 1/4" TRS Balanced Line Output
2 x 1/4" TRS Balanced/Unbalanced Line/Headphone/Re-Amp Output (Shared with Rear Panel Input)
1 x 1/4" TRS Headphone Output
1 x 1/8" / 3.5 mm TRS Headphone Output

Digital Audio I/O

2 x TOSLINK Optical ADAT Input
2 x TOSLINK Optical ADAT Output

Host Connection

1 x USB-C (Class-Compliant)

OS Compatibility

macOS 10.13 or Later
Windows 10 or Later
**As of October, 2023: Check with manufacturer for the most up-to-date compatibility*

Power Requirements	AC/DC Power Adapter (Included)
--------------------	--------------------------------

Channels of I/O	32 Inputs / 28 Outputs
-----------------	------------------------

Built-In DSP	Yes
--------------	-----

Maximum Sampling Rate	192 kHz / 24-Bit
-----------------------	------------------

Number of Microphone Inputs	2
-----------------------------	---

Built-In Microphone	No
---------------------	----

Input Level Adjustment	Knob
------------------------	------

Expansion Slots	No
-----------------	----

Signal Processing

Pad	Mic: -20 dB (Switchable per Channel) Line: -12 dB (Switchable per Channel) Line: -10 dB (Switchable per Channel) Hi-Z: -10 dB (Switchable per Channel)
-----	---

Solo/Mute	Solo, Mute per Master
-----------	-----------------------

Connectivity

Analog Audio I/O	16 x 1/4" TRS Balanced Line Input 2 x Combo XLR-1/4" TRS Balanced Mic/Line/Hi-Z Input (Front Panel) 1 x 1/8" / 3.5 mm TRS Line Input (Front Panel) 10 x 1/4" TRS Balanced Line Output 2 x 1/4" TRS Balanced/Unbalanced Line/Headphone/Re-Amp Output (Shared with Rear Panel Input) 1 x 1/4" TRS Headphone Output 1 x 1/8" / 3.5 mm TRS Headphone Output
------------------	--

Phantom Power	48 V, Selectable On/Off
---------------	-------------------------

Digital Audio I/O	2 x TOSLINK Optical ADAT Input 2 x TOSLINK Optical ADAT Output
-------------------	---

Host Connection	1 x USB-C (Class-Compliant)
-----------------	------------------------------------

Host Connection Protocol	USB 2.0
--------------------------	---------

USB (Non-Host)	3 x USB-A (External Storage, MIDI I/O)
----------------	---

Sync I/O	1 x BNC Word Clock Input 1 x BNC Word Clock Output 1 x 1/8" / 3.5 mm Clock Output
Network I/O	No
MIDI I/O	1 x DIN 5-Pin Input 2 x DIN 5-Pin Output/Thru
Wireless	No

Performance

Frequency Response	Line Inputs: 20 Hz to 20 kHz ± 0.06 dB Hi-Z Inputs: 20 Hz to 20 kHz ± 0.1 dB Mic Inputs: 20 Hz to 20 kHz ± 0.08 dB Monitor Outputs: 20 Hz to 20 kHz ± 0.02 dB Line Outputs: 20 Hz to 20 kHz ± 0.04 dB
Maximum Input Level	Line: +24 dBu (Rear) +22 dBu (Front) Hi-Z: 20 dBu Mic: 22 dBu
Maximum Output Level	Monitor: 20 dBu Line: 24 dBu Headphone: 14.4 dBu

Headphone Output Power

271 mW into 33 Ohms

Impedance

Line Inputs:
20 Kiloohm
Hi-Z Inputs:
1.1 Megohm
Mic Inputs:
2.7 Kiloohms
Monitor Outputs:
240 Ohms (Balanced)
120 Ohms (Unbalanced)
Line Outputs:
240 Ohms (Balanced)
120 Ohms (Unbalanced)
Headphone Outputs:
5 Ohms

Dynamic Range

Line Inputs:
118 dBA
Hi-Z Inputs:
114 dBA
Mic Inputs:
117 dBA
Monitor Outputs:
126 dBA
Line Outputs:
120 dBA
Headphone Outputs:
109 dBA

THD+N

Line Inputs:
-113 dBA
Hi-Z Inputs:
-105 dBA
Mic Inputs:
-110 dBA
Speaker Outputs:
-114 dBA
Line Outputs:
-106 dBA
Headphone Outputs:
-103 dBA

EIN

-129.5 dBu A-Weighted

Sample Rates	44.1 / 48 / 88.2 / 96 / 176.4 / 192 kHz
Bit Depths	24-Bit
Sync Sources	ADAT, Internal, Word Clock

Audio Storage & Playback

Media/Memory Card Slot	No
------------------------	----

Compatibility

OS Compatibility	macOS 10.13 or Later Windows 10 or Later <i>*As of October, 2023: Check with manufacturer for the most up-to-date compatibility</i>
Included Software	No
Processor Requirement	Mac: Intel Core i5 Apple M1
RAM Requirements	4 GB
Storage Requirements	4 GB

Mobile App
Compatible

No

**As of October, 2023: Check with manufacturer for the most up-to-date compatibility*

Power

Power Requirements

AC/DC Power Adapter (Included)

AC/DC Power Adapter

Included

Physical

Rackmount Size

1 RU (with Included Hardware)

Dimensions

17.3 x 11.6 x 1.7" / 43.9 x 29.5 x 4.3 cm

Packaging Info

Package Weight

11.37 lb

Box Dimensions (LxWxH)

23.9 x 13.4 x 5.4"