logo not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

Bowers & Wilkins AM-1 White

Šifra: 18088

Kategorija prozivoda: Outdoor Zvučnici

Proizvođač: B&W

Cena: 41.880,00 rsd



Performance that endures

AM-1 is entirely sealed, in order to keep the elements at bay. It's tough and hard-wearing too, and its clever one-piece mounting system with 220-degree rotation means it's ready to perform wherever you want it to, come rain or shine.

Easy to install, great to listen to

A one-plug, simple-to-install mounting system means AM-1 is happy vertically or horizontally. Plus, smart engineering means AM-1 sounds great whichever way you choose to mount it.

Specified and built without compromise

With our trademark Nautilus tube-loaded 25mm aluminium dome tweeter and 130mm glassfibre mid/bass driver supplemented by an auxiliary bass radiator for solid, powerful bass response, AM-1 has sound and scale way beyond its compact dimensions.

Blares out the tunes no matter the weather while retaining a subdued, stylish look... delivers high performance audio in an incredibly resilient, versatile package. J.Volpe

engadget.com

Size & weight

Dimensions	Height: 310mm (12 1/4in) Width: 180mm (7in)	
Net weight	Depth: 210mm (8 1/4in) 4kg (8.8lb)	

Technical details

Technical features	Nautilus™ tube loaded aluminum dome tweeter Glassfiber cone bass/midrange Auxiliary Bass Radiator (ABR)
Description	2-way system with Auxiliary Bass Radiator (ABR)
Drive units	1x ø25mm (1in) aluminum dome high-frequency 1x ø130mm (5in) glassfiber cone bass/midrange
Frequency range	-6dB at 46Hz and 50kHz (wall mounted)
Frequency response	51Hz - 22kHz on reference axis (wall mounted)
Sensitivity	86dB (2.83V, 1m)
Harmonic distortion	<1% 200Hz - 20kHz (86dB, 1m)
Nominal impedance	8Ω (5.2 Ω min)
Recommended amplifier power	$20W$ - $100W$ into 8Ω on unclipped program