

## Neutrik NL4FXX-W-S

Šifra: 18148  
Kategorija proizvoda: Konektori  
Proizvođač: Neutrik

**Cena: 720,00 rsd**



<b>Product</b>	
Title	NL4FXX-W-S
Connector series	speakON 4 pole

<b>Electrical</b>	
Contact resistance	$\leq 2 \text{ m}\Omega$
Dielectric strength	2.8 kVac
Insulation resistance	$> 10 \text{ G}\Omega$ (initially)
Number of electrical contacts	4
Rating Europe	IEC 61984: 37 A 250 V AC
Rating USA	UL1977: 35 A 250 V AC
Rating Canada	CSA C22.2 No.182.3: 24 A 250 V AC

ATTENTION:

**This product is strictly not intended for use as an AC mains or power supply connector!  
CAUTION: NOT FOR INTERRUPTING CURRENT**

<b>Mechanical</b>	
Cable O.D.	6 - 12 mm
Lifetime	typically 5'000 mating cycles
Wiresize (mm <sup>2</sup> )	1.5 - 4 mm <sup>2</sup>
Wiresize (AWG)	17 - 11 AWG
Locking device	Twist lock
Termination	screw type terminals

<b>Material</b>	
Contact plating	Ag
Contacts	Copper Alloy
Insert	Polyamide (PA6.6)
Locking element	Zinc diecast
Shell	Polyamide (PA6) / TPE
Strain relief	Polyketone
Bushing	Polypropylene / TPE

<b>Environmental</b>	
Temperature range	-33 °C to +80 °C
Protection class	IP20
Flammability acc. to UL94	V-0