Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Briteq BT-THEATRE 200TW

Šifra: 18315
Kategorija prozivoda: TV i Pozorišna Rasveta
Proizvođač: BRITEQ



Cena: 70.680,00 rsd

General : Weight (kg)	7.2
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	105
General : Color	black
General : Display	LCD
General : Fixation	M12
General : IP rating	indoor
Control : Modes	standalone fixed, manual, DMX
Control : Protocol	DMX, Wireless DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : minimum DMX channels	1
Control : maximum DMX channels	5

Light : lamp socket	No
Light : Lux	1850 (@ 5m beam 12°)
Light : lamp	COB
Light : min. color temperature (K)	2800
Light : max. color temperature (K)	6000
Light : CRI	95
Light : colors	White, Cold white, Warm white
Light : mix colors	Yes
Light : functions	manual focus, manual zoom
Light : min. beam angle (°)	12
Light : max. beam angle (°)	56
Light : max. refresh rate (kHz)	4.8
Connections : input	3 pin XLR, 5 pin XLR, wireless DMX optional, usb, PowerCon® or compatible
Connections : output	3 pin XLR, 5 pin XLR, usb, PowerCon® or compatible

Powerful 200W LED theater Fresnel with adjustable CCT.
Dual LED (100W 2800K + 100W 6000K) for tunable white with CCT ranging from 2800K to 6000K !
The perfect all-round projector for TV-work, theatre, rental, exhibition booths!
Exceptional photometric / price performance: CRI/Ra> 96, TLCI >98, CQS >96, Rf >94, Rg >100 (@3000K)
Manual beam angle adjustment: 12° ~ 56° (field angle: 20° ~ 67°)
Manual CCT presets while used in standalone: 2800K, 3000K, 3200K, 4000K, 4300K, 5600K, 6000K
Color frame for use of color filters and eight-leaf barndoor included.
No more heavy and expensive dimmer packs needed!
Very silent operation: temperature controlled, low noise cooling fan.
LCD-display to navigate easily through the setup menu!
Manual or DMX-controlled: 5 different channel modes (8bit & 16bit dimming) for maximum flexibility.
Can be used 1 channel DMX mode, with CCT-preset of your choice.
Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE !
Flicker free TV-recordings thanks to adjustable LED refresh rate: 600 Hz to 4800 Hz!
Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
Selectable lamp behavior: halogen lamp (slow) or led (fast).
Four dimmer curves: linear, square, inverse square, S-curve.
In case of DMX failure, you can choose between manual, blackout and freeze mode.

RDM-functionality for easy remote setup & monitoring: DMX addressing, channel mode, temperature, ...

Lock function to avoid unwanted altering of the settings.

Default factory settings + user settings can be saved/loaded.

3 & 5pin DMX in/outputs + PowerCON® compatible in/outputs for easy daisy chaining.

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.