Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

MARTIN AUDIO ACP-55T

Šifra: 18370
Kategorija prozivoda: Viseći Zvučnici
Proizvođač: Martin Audio



Cena: 33.480,00 rsd

Features

High performance two-way pendant speaker

5.25” (135mm) LF driver and 0.75” (19mm) HF dome tweeter

Wide 150° conical coverage pattern reduces speaker count required for even coverage

70V/100V multi-tap line transformer or 16-ohm low-impedance operation

Low and high-frequency overload protection

Quick release, bezel-less grille

UL94V-0 rated baffle and enclosure

5-year warranty

Applications

Retail outlets

Cafes, bars and restaurants

Museums and Houses of Worship

Hotels, casinos and concourses

Exhibition spaces and convention centres

Transportation facilities

The ACP-55T brings full-frequency response, consistent coverage and intelligibility to a wide range of architectural environments — from hotel atriums and exhibition spaces to retail outlets, bars and restaurants.

Comprising a 5.25” (135mm) LF driver and a 0.75” (19mm) silk-dome tweeter, the ACP-55T produces 109dB peak output at 1 metre and delivers superb sound quality for both music and speech reproduction. Its stylish pendant enclosure is equipped with a single-point mounting system plus provision for attaching a safety cable.

The consistent and wide 150° conical coverage of the ACP-55T reduces the number of speakers required for even coverage — leading to a reduction in installation cost.

It incorporates a high-quality transformer for 70V/100V line operation, with transformer taps selected by a rotary switch at the top of the pendant enclosure. The switch also provides for 16-ohm low impedance operation — enabling four or more speakers to be driven in parallel from a single amplifier channel. For full-bandwidth protection, the low and high- frequency sections are individually protected against overload by auto-resetting thermal fuses.

The grille is bezel-less for a clean look, its bayonet fitting is easy to remove without the use of tools and finished in white or black to match ADORN on-wall loudspeakers and may also be painted to blend with any décor.

TYPE	Passive two-way pendant speaker, ported bass reflex
FREQUENCY RESPONSE (1)	98Hz-20kHz ± 3dB -10dB @ 56Hz
DRIVERS	LF: 5.25” /1” high-temp voice coil, coated paper cone, rubber surround, ferrite motor, pressed steel chassis HF: 0.75” silk dome, neodymium motor
RATED POWER (2)	50W AES, 200W peak
RECOMMENDED AMPLIFIER	VIA2004 (for low-impedance operation)
SENSITIVITY(4)	86dB / 1W(4V) / 1m (full space)
MAXIMUM SPL (9)	109dB peak
NOMINAL IMPEDANCE	16Ω
DISPERSION (-6dB)	150° conical up to 7kHz
CROSSOVER	3kHz passive (LF and HF auto-resetting fuses

TRANSFORMER TAPS	70V: 30w / 15w / 7.5w / 3.75w 100V: 30w / 15w / 7.5w
RECOMMENDED HIGH-PASS FILTER	60Hz 24dB/oct
ENCLOSURE	UL 94V-0 rated ABS baffle and enclosure
FINISH	Black or white
GRILLE	Perforated steel, powder-coated, bayonet fitting
CONNECTORS	Ceramic connector (in and link)
DIMENSIONS	(OD) 246mm x (D) 238mm (OD) 9.7in x (D) 9.35in
WEIGHT	3.46kg (7.62lbs)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.